



PAPAGENO

Configuration,
Installation
and Administration

Version 5.9

Microsoft® and Windows® are registered trademarks of the Microsoft Corporation.
The remaining hardware and software designations mentioned in this book are in most cases also registered trademarks and so are subjected to the statutory provisions.

VIPcom GmbH
Ruedesheimer Str. 7
80686 Munich
Phone: +49 89 54750-0
Fax +49 89 54750-200
e-mail: info@vipcomag.de
<http://www.vipcomag.de>

The use, reproduction or distribution of the program is subject to the restrictions described in your contract with VIPcom GmbH

The specifications contained in this book are subject to correction and may be altered without any further notification.

VIPcom GmbH does not thereby commit itself to any further obligations.

Version 5.9

Copyright© 2016 VIPcom GmbH. All rights reserved

Content

Overview	3
A. Configuration Planning	11
1. Which Computer Do you Use for the PAPAGENO Installation on Windows?.....	13
2. Which Computer Do You Use for the PAPAGENO Installation on Linux/Unix?.....	15
3. Which Phone System Do you Have or Need?	16
4. Which Devices are Used?.....	21
5. How Many Lines are Required?	23
6. How to Connect PAPAGENO to your Mail System	25
7. If No Mail Gateway is Used.....	27
8. Document Conversion	28
9. How To Retrieve Messages by Phone	32
10. How To Reduce the Main Computer's Workload	34
11. To Guarantee the PAPAGENO Availability	35
12. To Achieve High Performance Fax Transmission.....	39
13. To Send Faxes Inexpensively from Various Locations	40
B1. Installing PAPAGENO on Windows	45
1. Prior to Installation	47
2. PAPAGENO is Easy to Install.....	48
3. Installed With PAPAGENO are	50
4. How to install a User-friendly Administration Program.....	53
5. How to Install a Single PAPAGENO Server	54
6. How to Install a PAPAGENO Mail Gateway.....	55
7. Starting and Stopping the PAPAGENO Servers.....	56
8. How to Install an Update Version	57
9. How to Handle a Large Number of Documents	58
10. How to Deinstall PAPAGENO	60
11. How to Install Devices	61
12. How to Install FAX Clients	62

B2. Installing PAPAGENO on Linux/Unix	63
1. Prior to Installation	65
2. PAPAGENO is Easy to Install	67
3. After Installation	69
4. How to Establish a Sandbox	71
5. Installed With PAPAGENO are:	72
6. How to Install an Update Version	75
7. Large Number of Documents.....	76
8. Starting and Stopping the PAPAGENO Servers	77
9. Deinstallation of PAPAGENO	78
10. How to Install a Single PAPAGENO Server	79
11. How to Install Devices	81
12. Providing Access to the Mail Server.....	83
13. How to Install FAX Clients	84
 C. Administer PAPGENO	 85
1. PAPAGENO Administrator	87
2. Assigning an Administrator Password.....	91
3. Registering the PAPAGENO Servers	92
4. Registering Users	96
5. Registering Devices and Device Drivers	103
6. Setting Up Services in PAPAGENO	104
7. Registering ISDN Cards	106
8. Registering a PAPAGENO Communication Server	112
9. Registering a Modem.....	113
10. Enter at Least One Distribution Rule	115
11. PAPAGENO is now ready to use!.....	116
12. How to Deliver an Incoming Message to Several Users	117
13. Entering Additional Distribution Rules.....	118
14. If Faxes Are to be Printed.....	120
15. How to Forward Faxes Free of Charge to a Remote PAPAGENO Installation	121
16. How to Use Fax Number Mapping or Call by Call	122
17. Storing Messages in PAPAGENO	124


D. Configure PAPGENO 127

- 1. Connecting PAPAGENO to the Mail System 128**
- 2. Preparing the User Computers 129**
- 3. How to install comFAX/Win 130**
- 4. How to Install the Fax MAPI Printer 132**
- 5. How to Setup the RedMon Printer 134**
- 6. Configuring Telephone Access to Messages 139**
- 7. How to Install other FAX Clients 140**

Index 141

General

PAPAGENO provides an interface between a mail server and a TC system. All messages and user addresses are stored centrally and can be administrated easily.



PAPAGENO is flexible

- Via mail gateway PAPAGENO can be integrated into any SMTP compliant mail system.
- High-performanced device drivers connect PAPAGENO to ISDN cards or modems.
- Via interfaces PAPAGENO can be integrated to external systems and internal applications.
- PAPAGENO is compatible with many platforms on the Linux, Unix and Windows operating systems and can be made reliable.
- PAPAGENO can be clustered and extended as required.
- For each PAPAGENO communication computer up to 90 channels can be used. Several PAPAGENO communication hosts can operate in parallel.

Mobile Access is no problem with PAPAGENO.

PAPAGENO Configuration , Installation and Administration - Overview

You **have to** plan or do in any case

You **can** plan or do additionally

1. Planning the Configuration

Which **computer(s)** do you use ?

Which **phone system** do you use?

Which **devices** do you use ?

How many **Lines** are required ?

How to connect PAPAGENO to your **mail system** ?

Where documents will be **converted into fax format** ?

Do you want to retrieve messages by **phone**?

Do you want to **reduce** the main computer's workload ?

Do you want to be sure that PAPAGENO is always available (**Backup concept**)?

Do you want to achieve high performance fax transmission

Do you want to send faxes inexpensively from various locations (Least cost routing)

2. Installing PAPAGENO

Execute the **main installation**
(Installed together with PAPAGENO are :
all PAPAGENO servers, drivers, commands,
software interfaces, ASCII administration
programm comfax -adm)

Install the **devices**

Installing single **PAPAGENO server processes**
(e.g. THETA server for devices)

Securing **access to the mail server**
(Installing **mail gateway** or **MAPI connector**)

Installing an **Administration programm** with
graphically interface

Installing **comFAX clients**

3. Administer PAPAGENO

with one of the Administration programs : Admin/Win, or Web-Admin or comfax-adm

Enter:

Servers (Computers, on which PAPAGENO is installed)

Users

Devices with corresponding device drivers
(Fax, Fax/Voice Telex, SMS, depending upon device)

at least one **distribution rule**

Enter:

User groups

Additional distribution rules

Number mapping

... and PAPAGENO works!



A. Configuration Planning

1. Which Computer Do you Use for the PAPAGENO Installation on Windows?	13
Software Requirements	13
Hardware Requirements:	13
Disk Space for Faxes	13
Network Requirements:	13
Devices Requirements	13
Further Requirements	14
2. Which Computer Do You Use for the PAPAGENO Installation on Linux/Unix? . . .	15
Software Requirements:	15
Hardware Requirements:	15
Disk Space for Faxes	15
Network Requirements:	15
Devices Requirements	15
3. Which Phone System Do you Have or Need?	16
Digital Phone System	17
IP Phone System	19
4. Which Devices are Used?	21
Which Computer is Used for Devices?	22

5. How Many Lines are Required?	23
6. How to Connect PAPAGENO to your Mail System	25
7. If No Mail Gateway is Used.....	27
8. Document Conversion	28
How to Convert Documents on the Gateway System	29
How to Convert Documents on the Clients	30
9. How To Retrieve Messages by Phone	32
Retrival of Faxes and Voice Mails	32
Retrival of the Faxes, Voice Mails AND Mails	33
10. How To Reduce the Main Computer's Workload	34
Why Relocate ALPHA Servers?.....	34
Printer Clients.....	34
11. To Guarantee the PAPAGENO Availability	35
Devices and High Reliability.....	36
If You Prefer a More Simple Solution... ..	37
The Simplest Solution for Devices... ..	38
12. To Achieve High Performance Fax Transmission	39
13. To Send Faxes Inexpensively from Various Locations	40
14. To connect the Fax System with your Process Control Application Software . .	41
15. Sending Dokuments from Applications Directly	41

1. Which Computer Do you Use for the PAPAGENO Installation on Windows?

Software Requirements

- minimum Windows® 2000 or higher
- NTFS partition for the PAPAGENO installation

Hardware Requirements:

- Pentium system, as efficient as possible, 200 MHz minimum
- 300 MB minimum disk storage
- 256 RAM minimum (accordingly more in case Microsoft Office is started to open fax transition)

The higher the number of open lines the higher the efficiency of the computer must be.

Disk Space for Faxes

Producing a fax means image processing. Note that each page stored on the server requires about 60 KB; 10,000 pages require about 600 MB. Therefore take into account the number of documents and the storage duration for planning. If a mail gateway is used pages reside in memory temporarily but are not stored.

If your messages (faxes, telexes, voice mails) have to be saved in PAPAGENO you need:

- Sufficient disk space for those documents.

Network Requirements:

- A TCP/IP based network

Devices Requirements

As devices you need: slots for ISDN cards (PCI 2.1, full height) and/or a corresponding number of serial interfaces (V.24) for the connection of fax modems.

The serial interfaces must be modem-capable. The possible transmission rate must at least be 19.200 bauds per second.

Further Requirements

- DNS name can be resolved
- It is recommended to define an alias name for the PAPAGENO computer, e. g. "message server" and to enter this alias name during the installation.
- A connection to the telephone network exists.
PAPAGENO has to be connected via one or several PRI or BRI connections and CAPI with the **public telephone network**. This connection is realized either via a TC system or a telephone provider.
- A **CAPI interface** exists on the PAPAGENO device computer.
- A **mail server** is installed and configured.

If you plan the configuration with an IMAP and an LDAP connection between device server and mail server:

- ▶ Make sure that the services LDAP and IMAP4 are configured in your mail server.

2. Which Computer Do You Use for the PAPAGENO Installation on Linux/Unix?

Software Requirements:

- A Linux or Unix operating system must be installed.
The current platform versions, compatible with PAPAGENO are listed on our web site www.vip-comag.de under Products - PAPAGENO - Versions

Hardware Requirements:

- 300 MB minimum disk storage for the basic installation of PAPAGENO
- 256 RAM minimum

The higher the number of open lines the higher the efficiency of the computer must be.

Disk Space for Faxes

Producing a fax means image processing. Note that each page stored on the server requires about 60 KB; 10,000 pages require about 600 MB. Therefore take into account the number of documents and the storage duration for planning. If a mail gateway is used pages reside in memory temporarily but are not stored.

If your messages (faxes, telexes, voice mails) have to be saved in PAPAGENO you need:

- Sufficient disk space for those documents

Network Requirements:

- TCP IP based network

Devices Requirements

As devices you need: slots for ISDN cards (PCI 2.1, full height) and/or a corresponding number of serial interfaces (V.24) for the connection of fax modems.

The serial Interfaces must be modem-capable. The possible transmission rate must at least be 19.200 bauds per second.

3. Which Phone System Do you Have or Need?

Phone System	PAPAGENO	Services
analog	modem	fax
digital	ISDN card	fax, SMS, voice mail
IP system	CAPI VoIP protocol stack	fax, voice mail SMS

Analog Line

With an analog line you can use the **fax service** only.

Digital Line

A digital line permits the use of **all PAPAGENO services and features**: fax, SMS, voice mail, fixed network sms. Up to 30 channels and up to 1000 direct dial numbers are at your disposal. High fax volume is no problem. See below „Digital Phone System”, page 17.


IP Phone System

In case you handle telephony via Internet already (IP-PBX or ISP) you can use the services voice mail, SMS and fax without additional hardware by means of a protocol stack. See below „IP Phone System”, page 19.

Digital Phone System

Access Via TC System

An ISDN point-to-point connection must exist in the TC system. The TC system must support the cascading of private branch exchanges with internal connection code. Thus an ISDN card works like a system within the system.



The TC system evaluates the fax prefix (in the above example it is number 9), the device and PAPAGENO interprets the direct dial numbers.

If you have identical extensions at various locations (e.g. Munich and Sidney), PAPAGENO provides for messages being delivered correctly.


Make sure that for incoming calls the called number is signaled in the D channel. For this purpose the access must be realized via the DSS1 protocol.

Advantage: You can continue to use your "old" phone number structure. Internal call forwarding is possible. An incoming call can be forwarded to the voice box in case of lines being "busy" or "unavailable".

Disadvantage: Possibly higher installation and investment efforts.

Access Via Parallel-Connected External Lines

PAPAGENO is connected directly to the local loop:



The ISDN router and PAPAGENO evaluate the direct dial numbers.

If several S_0 or S_{2m} connections exist it is recommended to bundle them in parallel (= to bundle). Thus every termination will respond to the same number. The computer with ISDN cards or a router are connected directly to the S_0 or S_{2m} interface of the local loop.


Advantage: simple and low priced, standardized environment, easy to install.

Disadvantage: Internal connections are not possible. Forwarding and inquiring the voice box is only possible via the public telephone network.


If every user likes a personal voice box ...

... you will need a TC system in any event. If the number is "busy" or "unavailable" an incoming call will then be rerouted to the voice box.

IP Phone System



You can integrate PAPAGENO easily into that system:



A CAPI-VoIP protocol stack connects PAPAGENO to the IP phone system

In case you handle telephony via Internet already (IP-PBX or ISP) you can use the services voice mail, SMS and fax without additional hardware by means of a protocol stack. (Fax may be used if the IP Phone System supports T.38.)

If you want to send a high number of faxes, we recommend an ISDN card since the transmission time via Internet is more time absorbing than via PSTN.

Voice-Mail is processed via H.323 resp. SIP.

Faxes are sent via T.38

SMS is processed via H.323 resp. SIP. The IP phone system must support the SMS protocol.

4. Which Devices are Used?

PAPAGENO supports ISDN and analog devices.

Devices you can use with PAPAGENO

ISDN cards and routers	Dialogic (Eicon Diva) with Server BRI (S_0); Dialogic (Eicon Diva) with Server 4BRI ($4 \times S_0$); Dialogic (Eicon Diva) with Server PRI (S_2m). Funkwerk bintec RT1202 Media Gateway
PAPAGENO Communication Server	Pre-configured, S_2m cards.
GSM devices	Devices which can send/receive via GSM (e. g. mobiles with V.24-Adapter, wireless modul)
Telex devices	Telex adapter, Hasler
Modems	Any modems supporting class 2 standard

The ISDN router Brick / BinTec is still supported, but not sold any more by the company BinTec since the beginning of 2003.

The devices support the following services

ISDN card, router	Fax, fixed network SMS, voice mail
PAPAGENO Communication Server	Fax, fixed network SMS, voice mail
GSM devices	SMS (no fixed network SMS)
Telex devices	Telex
Modems	Fax

With an ISDN device you can use all PAPAGENO services (fax, voice mail, SMS).

Devices can be used with the following PAPAGENO installations and operating systems:

Device	Operating System
ISDN cards	Windows[®], Linux
PAPAGENO computer	Windows[®], Linux
Modems, GSM devices	Windows[®], Linux, Unix

Which Computer is Used for Devices?

Devices can connect or be attached to a PAPAGENO host or to a separate PAPAGENO system.

In any case a PAPAGENO device server (**THETA**) and a device driver must be installed on the "device computer".

The following software is required on the device computer:

ISDN card	ISDN cards need a CAPI interface and therefore are running on Windows® and Linux.
GSM device, modem, telex	The PAPAGENO drivers are running on all platforms.

Text-to-Speech can be used on **Windows® and Linux** since both the PAPAGENO Scripting Engine and the Text-To-Speech software from Acapela (former Elan) are running on Windows® and Linux.

The following hardware is required on the device computer:

ISDN card	Slot, S₀- or S₂- interface. No other CAPI applications must be installed on this computer.
GSM device	Serial interface (V.24)
Modem	According number of serial interfaces (V.24). Interfaces must be modem-compatible. The minimum transmission rate is 19,200 bauds per second.

NOTE: PAPAGENO must have exclusive rights for all its devices. If other application programs can access these devices this may affect the performance of PAPAGENO.

5. How Many Lines are Required?

The more lines you use, the more messages you can send and receive in a short time period.

The number of lines depends on the kind of device being used.

The devices provide the following number of lines

Dialogic (Eicon) Diva server S ₀ card	2 channels
Dialogic (Eicon) Diva server S _{2m} card	30 channels
Dialogic (Eicon) Diva server 4 BRI S ₀ card	4 or 8 channels
Dialogic (Eicon) Diva server S _{2m} card	30 channels
Funkwerk bintec RT1202, 2 BRI S ₀ card	4 channels
PAPAGENO communication server	30, 60, 90 or 120 channels (by request 2 or 8 channels)
GSM device, modem, telex device	1 channel

Fax examples:

1 line: approx. **60** pages per hour

30 lines: **1,800** pages per hour or 18,000 per day (10 hours)


These specifications may vary if a dialled number is busy and the dialling procedure has to be repeated.

VIPcom provides a licence for a certain number of channels ("lines"). Enter the appropriate number of lines setting up the device drivers for each device. Be aware that the total number of lines you enter does not exceed the total number of licences.

Fax and voice mail may use the same lines. Enter the number of licensed lines for the fax/voice driver.

6. How to Connect PAPAGENO to your Mail System

A **mail gateway** establishes the connection between PAPAGENO and the mail server.



Which mail system can be used?

The "PAPAGENO-SMTP-Gateway" works with any mail server whose communication functions via port 25. It is platform-independent and can use MAPI on Windows® for document conversion.

For the different mail systems there used to exist dedicated gateways, e. g for Exchange. The PAPAGENO-SMTP gateway is compatible with the Exchange mail server 2007 and higher.

If you do not use a mail server the PAPAGENO MAPI Connector connects the Outlook® user interface to PAPAGENO (see below Chapter 7. „If No Mail Gateway is Used...“, page 27).

Is it possible to use an existing user database?

Yes, the records may be extended to include fax, voice mail or SMS addresses.

Do you use a directory server?

If yes, PAPAGENO, via LDAP, has access to user data and fax numbers on your directory server.

If no, save the numbers of your users for fax, SMS and voice mail in PAPAGENO.

On which platforms does the gateway run?

It is platform-independent, but can use MAPI for document converting under Windows®.

On which platform the PAPAGENO server can be installed?

On Windows® or Linux/Unix, independently of the platform where the gateway is installed.

Do you need multiple mail gateways?

No, not normally. At extremely high bandwidth (numerous messages in a short time), broadcast clients, or frequent serial fax transmissions multiple gateways may be useful.

The PAPAGENO SMTP Gateway can parallel manage messages for multiple SMTP mail servers.

Which formats can be converted by the SMTP gateway?


Common formats (like PostScript, ASCII, TIF as well as PCL, HPGL, PostScript Level 2 if licensed) can be converted to fax format via the gateway. Via MAPI also the formats of the Windows® applications such as: .doc, .xls, .pdf can be converted.

7. If No Mail Gateway is Used...

.. documents must be converted to fax format on the user computers. After this they can be forwarded to PAPAGENO. (See below Chapter 8. „Document Conversion“, page 28).

Windows User Computers

Users create documents in any Windows applications and send them to the FAX MAPI Printer that converts the documents and forwards them via the PAPAGENO user interface comFAX/Win or via Outlook/PAPAGENO MAPI Connector to PAPAGENO.



The **FAX MAPI Printer** is part of the PAPAGENO MAPI connector but can be separately installed.

The **PAPAGENO-MAPI Connector** connects Outlook with PAPAGENO. It also converts send documents to fax format. Nevertheless the connector only works with an Outlook Version that is lower than 2010 (32 Bit) and therefor is hardly used anymore.

Send Faxes from Applications

Documents can be sent from Windows- or Linux applications directly.

(See below Chapter 15. „Sending Dokuments from Applications Directly“, page 42).

Conclusion:

Without mail gateway use the virtual PAPAGENO printer **FAX MAPI Printer** for document conversion together with the PAPAGENO client **comFAX/Win**.

For unified messaging you should consider a mail gateway in order to benefit from all features

8. Document Conversion

Normally faxes are created in a graphical or a word processing program.


The conversion to fax format is performed

- either on the gateway system via the PAPAGENO MAPI Connector and/or PAPAGENO Tools
- or on the client via a PAPAGENO Printer

If a PAPAGENO MAPI Connector is installed on the client it will convert the regarding documents into fax format.

How to Convert Documents on the Gateway System

A fax document that have been created in a Windows® application can be sent as an email attachment to a fax address. On the gateway system it is then converted to fax format by a **PAPAGENO tool** or by the **PAPAGENO MAPI Connector**.



*. pdf conversion

pdf and html documents will be converted via PAPAGENO Tools and freeware programs

*. doc conversion:

Windows formats (except of pdf) will be converted by the PAPAGENO MAPI Connector. Since the PAPAGENO MAPI Connector needs an according Windows® converting program on the gateway system all of the Windows® applications from which users may send faxes have to be installed. To avoid problems the server version must be compatible with the client versions.

Advantage:

- The CPU load for conversion is on the gateway system.
- For pdf and html conversion you only have to install the freeware and to activate the tools
Note that each office document can reach Outlook as a pdf.

Disadvantage:


- Using the PAPAGENO MAPI Connector: Installation and maintenance of the regarding Windows® applications on the gateway system

How is the PAPAGENO MAPI Connector Installed?

It is included with PAPAGENO delivery and is installed easily. All you need to do is to indicate the PAPAGENO host and the user name.

How to Convert Documents on the Clients

Documents can be created in applications and converted directly to a fax.



On Windows, the FAX MAPI Printer (driver) converts the documents. It is part of the PAPAGENO MAPI connector.

FAX-MAPI Printer

The user selects the FAX-MAPI Printer in the application in which he has prepared the document. This converts the document into fax format and passes it to the mail client. There it resides as a document with the extension *.tif and can be viewed immediately or be sent to a fax address.

Advantages:

- The user sees the document in the mail send window as it has been sent. (Tiff format)
- No programs have to be maintained on the gateway system
- Insurance against macro viruses
- Version incompatibilities are avoided

Disadvantage:

- The burden of conversion is on the user's computers.
- A FAX-MAPI Printer has to be installed on each user computer.

On Unix, there are special PAPAGENO / comFAX Printers (drivers), that convert ASCII and PostScript documents. Also they send documents from Unix applications to PAPAGENO in fax format.

Which Formats Can be Converted by the Fax-MAPI Printer?

Any formats that are supported by the OLE interface or anything that is printed from a Windows system can be converted to a fax format.

9. How To Retrieve Messages by Phone


In order to retrieve messages by phone there are two possibilities:

Configuration with mail server	Configuration without mail server
All messages are stored on the mail server. PAPAGENO will access them via IMAP.	You can access all faxes and voice mails, because they are stored in PAPAGENO.
For this configuration you need: PAPAGENO mail gateway, Directory-Server, LDAP, IMAP4	For this configuration you only need PAPAGENO. A mail gateway is optional.

Retrival of Faxes and Voice Mails

In PAPAGENO you can specify that all incoming faxes and voice mails are to be stored both on the PAPAGENO server and the mail server.

The disadvantage of this solution is that messages are kept twice: on the mail server and the PAPAGENO server. Thus double disk space is required and administrative efforts are higher. Email cannot be retrieved by phone because they are stored on the mail server only.




Retrival of the Faxes, Voice Mails AND Mails

PAPAGENO supports access to mail systems via an IMAP4 interface.

With an **IMAP4 link** between the PAPAGENO device and the mail server all messages (faxes, voice mails AND mails) can be retrieved by phone.

All messages are stored on the mail server (and exclusively there). Together with an text-to-speech-application users can also be notified of mails and have their mail texts read out.



User addresses (mail, fax and voice numbers) are stored on the mail system's directory server. This server can be accessed from the gateway and the PAPAGENO device via **LDAP**.

The advantage is that addresses are only stored once.

If you plan to store all messages on the mail server sufficient disk space must be available on this server (one page of a document requires about 60 KB; this adds up to 600 MB for 10000 pages).

10. How To Reduce the Main Computer's Workload

Certain parts of PAPAGENO (server processes) can be relocated as follows:

- **ALPHA servers** to computers where users are managed.
- **THETA servers** to computers where devices are connected/mounted.
- **PI servers** to computers to which the PAPAGENO printers are connected.
- Under Unix you can install separate **print clients**.

Individual PAPAGENO servers can also be installed on **Unix computers**, even if the main installation is running on a **Windows® computer** and vice versa. You can mix the platforms on which PAPAGENO runs in any way you like.

To install an individual server you will need the PAPAGENO version for the desired platform.

Why Relocate ALPHA Servers?

Because the computer on which the OMEGA server is installed does not have sufficient disk space for the user's documents.

You may want to manage users by department. (Each department has a computer on which its users and their documents are managed.)

Please note: If all fax documents and voice mails are stored on the mail server, less space is required on the ALPHA computer.

A THETA server must be installed on **every computer with a mounted or connected device**.

A PI server must be installed on **every computer to which a printer is connected**.


Printer Clients

`comfaxpr` and `comfaxps` printer clients are responsible for the creation of PAPAGENO documents. You can use them to send faxes from the shell.

Printer Clients are installed separately to unburden the fax computer.

11. To Guarantee the PAPAGENO Availability

... employ the following **back-up concept**: use the high availability solution of the operating system.




The high availability solution of the operating system provides that one computer takes over as soon as another one fails. Data kept failsafe as well when a "double ported RAID system" is used.

PAPAGENO is installed on an failsafe system: Host A accesses all PAPAGENO processes. If Host A fails, an identical PAPAGENO installation will be started on Host B. For this purpose the high availability solution of the operating system provides the appropriate resources.

The high availability solution may consist of two separated networks. Both Host A and Host B are connected to these networks. If one network fails the other one will take over.

Devices and High Reliability

without having to purchase and install everything twice!



Set up $n+1$ communication server.

$n+1$ means that you set up one communication server in addition to those needed for sending and receiving messages. If one server fails there will still remain enough lines to communicate.

A communication server is a computer with one or more fax cards (2 to 200 lines) (or one or more Bricks) and one PAPAGENO THETA server process.


Example: You need 90 lines. => You have to set up 4 communication servers with 30 lines each.

All communication servers are connected with **both networks**. If one network fails the services will continue without a break.

All communications servers are connected to different nodes of the public switched telephone network (PSTN). => thus high reliability is guaranteed as well.

If You Prefer a More Simple Solution...

... use the simple backup concept



PAPAGENO is installed on a failsafe hddisk system.

Host A and Host B are responsible only for any server processes of the PAPAGENO servers ALPHA and OMEGA.


Databases, file systems and images of these server processes are located on a RAID system. Both Host A and Host B have access to this RAID system. Host A usually controls all fax operations. If it fails only the SCSI connector has to be switched for Host B to take over.

It is recommended to use **two identical computers** (harddisk, CPU, configuration). In any case it is essential to provide exactly the same PAPAGENO installation on both systems!

Not essential is the use of a RAID system. It is also possible to use a disk mirroring between Host A and Host B. If Host A fails simply the network address or the alias name of Host B has to be changed.

The Simplest Solution for Devices...

...is to redouble everything:




Two devices are connected each with a TC system and with different nodes of the public switched telephone network (PSTN).

Both devices can be used for normal operation. If either Host C or D fails, the other system will be available, although only **half of the lines** can be used.

In case that the TC system or a line fails, the device system of the other line can be used.

12. To Achieve High Performance Fax Transmission

... you can install several communication servers for load balancing.




One communication server is able to serve up to 120 lines. And one line receives or sends approximately 60 fax messages per hour. If you plan to handle 6,000 faxes per hour you will need 100 lines.

In the example shown above every communication server is connected to the TC system with 2 primary rate interfaces (PRI) connectors.

13. To Send Faxes Inexpensively from Various Locations

... use the “cellular concept”



This requires a **complete PAPAGENO installation** at each of your company's locations.

Every OMEGA server recognizes all ALPHA servers of all installations.

This means that a user at location 1 will find another user at location 2 in the user list and can forward a document to him.

Documents can thus be sent free of charge from one location to another (e.g. one in Sydney and one in Munich).


By setting up the so called **least-cost-routing** (permanent feature of PAPAGENO) you can also send faxes to another location **at local rates**.

Example: You have a branch in Munich and one in Sydney. From Munich you can, for example, send thousands of pool faxes to Sydney at local rates.

=> Least-cost-routing enables you to send documents to another location at local rates.

14. To connect the Fax System with your Process Control Application Software

The safe and simple PAPAGENO access to process control application software is realized by an XML interface.



For sending and receiving faxes a store with "projects" will be created. The process control application software places faxes to be send in the out-folder of the corresponding project. PAPAGENO XML Postman checks all outboxes, gathers all jobs and dispatches fax messages via the fax server. Feedback on the fax status will be placed in the in-folder of the corresponding project as well as incoming faxes.

For each incoming fax an XML file will be supplied, that contains all fax relevant data. The process control application software can be programed in such a way that the content of faxes and data can be selected and evaluated.

Fax as a Service

If you don't have or don't want to have a PAPAGENO installation inhouse: Make use of our powerful Unified Messaging server, PAPAGENO, available in highly qualified data centers.

In this case you only have to install the XML interface. We'll take care of the rest.

15. Sending Documents from Applications Directly

Documents can be sent from Windows- or Linux applications directly without any client. Users write send options like receiver fax number, solution, sendtime and priority in form of control commands into the dokument. A spezial PAPAGENO printer interprets and evaluates the control commands.

Via scripts and macros this process can be automated e. g. for busines processes.

Linux/Unix Applications

PostScript

A document with the entered control commands is sent to the PAPAGENO printer `faxps`, who interprets the commands, converts the documents into fax format and forwards it to PAPAGENO.

ASCII

With the ASCII printer `faxpr` faxes can be sent from applications that create ASCII documents. These documents can be formated with further control commands.

The Printer `faxpspr` differentiates between ASCII and PostScript and calls the required filter.

Die Drucker-Clients sind ausführlich im PAPAGENO-Handbuch „Schnittstellen“, Teil A beschrieben.


Windows-Applications

Documents from Windows applications (Microsoft Office, etc.) with entered control commands can be sent to the RedMon printer. RedMon is free software.

PostScript Documents

The RedMon printer converts the documents into PostScript format and forwards it to the PAPAGENO tool `psscan`.

`psscan` scans for control commands, reads them and forwards the document to the PAPAGENO printer `faxps`




`faxps` interprets the control commands, converts the document to fax format and forwards it with all send options to the PAPAGENO driver.

ASCII Documents

Documents from Windows applications can be converted to ASCII format and then be sent.

If the document contains no pictures this is the favourable alternative, for PostScript is licensed with costs.



The RedMon printer for ASCII converts the documents into ASCII format and forwards it to the PAPAGENO printer `faxpr`.

`faxps` interprets the control commands, converts the document to fax format and forwards it with all send options to the PAPAGENO driver.

The free software „Redmon“ must be installed on a user computer and configured as ASCII or PostScript printer. (See below „“, Kapitel „How to Setup the RedMon Printer“, Seite 134.)



B1. Installing PAPAGENO on Windows

1. Prior to Installation	47
2. PAPAGENO is Easy to Install	48
3. Installed With PAPAGENO are	48
Reserved User Names	50
comfax-adm Administration Program	50
PAPAGENO Commands	51
CMD-line Commands (Software Interfaces)	52
4. How to install a User-friendly Administration Program	50
5. How to Install a Single PAPAGENO Server	50
6. How to Install a PAPAGENO Mail Gateway	50
7. Starting and Stopping the PAPAGENO Servers	56
8. How to Install an Update Version	57
How to install an update	57
How to Install an ALPHA Server Update	57
9. How to Handle a Large Number of Documents	58
To Increase the Number of Subdirectories	58
How to Use the Variables	58
10. How to Deinstall PAPAGENO	60

11. How to Install Devices	50
Installing ISDN Cards	61
Connecting the PAPAGENO Device Computer to the Network	61
Setting Up Modems	61
12. How to Install FAX Clients	62

1. Prior to Installation ...

... pay attention to the following **requirements**:

- A connection to the telephone network exists
PAPAGENO have **access the public telephone network** via one or more PRI or BRI connections and CAPI. This link can be realized either by a TC system or a telephone provider.
- A **CAPI interface** on the PAPAGENO device computer exists.
- A mail server is installed and configured.

If you plan a configuration with an **IMAP and LDAP** connection between the PAPAGENO device and the mail server:

- ▶ First make sure that the LDAP and IMAP4 services are set up on your mail server.

On the computer on which you want to install PAPAGENO:

You have to install PAPAGENO as

- Windows administrator (Be shure that his name is `Administrator` - otherwise he will have no PAPAGENO rights)
 - or as system user `comfax` .
- ▶ Possibly create a user `comfax` and assign administrator rights to him.
 - ▶ Log in as administrator resp. as user `comfax`.
 - ▶ Close all programs.

If the Windows® server is also an Exchange server:

- ▶ Close Exchange as well.

Services not necessary for Windows® are running:

- ▶ Select the `Control Panel`. Open the `Services` window.
- ▶ Close all services which are not critical for Windows®.
Pay special attention to RPC-based applications (CD-ROM server, archiving systems) which install their own port mapper. Only one port mapper is allowed to run on each Windows® system. You may be able to replace the port mapper of the particular system by the PAPAGENO port mapper.

Otherwise installation problems may occur!

2. PAPAGENO is Easy to Install

- ▶ In our Website open via Downloads PAPAGENO - Software packages - PAPAGENO-Server Version 5.9 the PAPAGENO server versions of the several operating systems.
- ▶ Unzip Server_Windows_5_9.zip
or
- ▶ insert your PAPAGENO CD, click on Continue and then click on Search.
You get all directories.
- ▶ Change to the Server directory.
- ▶ Select Setup and click Complete.

Usually you accept all the default settings (left column, bold) with the button **Next**:

Deutsch English	installation language
C:\FAXSERVER	installation directory
System server (OMEGA) User server (ALPHA) Device server (THETA) Printer server (PI)	Server components. All components except for the OMEGA server can be deactivated.

- ▶ Enter the license key.

Germany Other countries	Country in which PAPAGENO is being used, can be changed later.
None SMTP MAPI	No mail notification Mail notification (if you use a gateway you will receive mail notifications for faxes anyway) Do not use (will be handled with the MAPI profile)
Deutsch English Francais	Language for user interfaces, can be changed later.
8859 Charset Other character sets	(Default character set, can be changed later).

- ▶ Complete the installation protocol. After installation it is sent to VIPcom GmbH as a fax.
The installation is now complete.
Once you confirm your entries with Done. PAPAGENO will be started automatically.

The fax server will now be managed as a service by Windows[®]. Fax servers are automatically started when Windows[®] starts and shut down when Windows[®] shuts down.

3. Installed With PAPAGENO are

- All of the **PAPAGENO server processes**
(ALPHA, OMEGA, THETA, PI, LAMBDA, NUE, GAMMA)
- PAPAGENO **drivers for devices**
- The **PAPAGENO-SMTP-Gateway**.
It is unlocked by entering the license key and can be activated by a configuration variable (see Manual „PAPAGENO-SMTP-Gateway“)

PLEASE NOTE: Prior to Version 5.2, PAGENO was called comFAX!
Thus comFAX often appears in internal names and commands.

Reserved User Names

User name	Description
User comfax	comfax is a sample user in PAPAGENO.
System administrator FAXADM	The user FAXADM has access to the documents and telephone books of all users handled by an ALPHA server. This user should be protected by a dedicated password.
user .winpr	The user <code>.winpr</code> is the owner of all documents spooled to the <code>faxps</code> or <code>faxpr</code> printer via the THETA server. As the user <code>.winpr</code> is preceded with a “dot”, this name does not appear in the PAPAGENO user list.
System administrator .routing	The user <code>.routing</code> is important for least-cost routing. As the user <code>.routing</code> is preceded with a “dot”, this user does not appear in the PAPAGENO user list.

comfax-adm Administration Program

Most of the important administration procedures can be operated via the **ASCII interface** of this program under Unix, Linux and Windows®.

The graphical interfaces of the administration program (PAPAGENO Windows-Administrator and Web-Administrator) must be installed separately (see below: 4. „How to install a User-friendly Administration Program”, page 53).

PAPAGENO Commands

The following list provides a description of the most important PAPAGENO commands:

Command	Description
<code>l_startserver alpha/</code> <code>l_stopserver alpha</code>	Starts respectively stops the ALPHA server on the local computer. All other servers can be started in the same way (e. g. <code>l_startserver omega</code>)
<code>l_startserver server/</code> <code>l_stopserver server</code>	<code>server</code> means the server names (omega, gamma, lambda, nue, pi, etc.). Starts and accordingly stops the named server on the local computer. Attention: <code>l_stopserver theta</code> does not exist . Use <code>t_shutdown</code> Instead (see below).
<code>t_shutdown</code>	Stops the THETA-Server. The current job on the corresponding device will be completed first!. When all drivers have been stopped, the THETA server will shut down . The completion of a current send or receive job will be finished currently but may take some time. Check this with the command <code>l_ps</code> when the shutdown has been finished.
<code>l_startfax</code>	Starts all configurable server processes on the local computer. To use <code>l_startfax</code> the LAMBDA server has to run first.
<code>l_stopfax</code>	Stops all server processes on the local computer - except for the LAMBDA server.
<code>l_startdrivers</code>	Starts all locally accessible drivers. The THETA server must be started separately with the command <code>l_startserver theta</code> . If the other servers are not accessible documents can be received this way. These documents will be saved locally until the responsible ALPHA server is accessible again.
<code>l_startdriver driver</code> <code>l_stopdriver driver</code>	Starts or stops the named driver. <i>driver</i> is the name by which the fax or telex driver equipment has been registered in the administration program. The driver <code>gd-capidrv</code> is finished automatically as soon as all lines are "dead".
<code>l_stopgateways</code>	Stops all local gateway processes
<code>l_startdaemon daemon</code> <code>l_stopdaemon daemon</code>	Starts/stops the according daemon process.
<code>l_startgateway gateway</code> <code>l_stopgateway gateway</code>	Starts/stops the according gateway process.

In the PAPAGENO-Web-Administrator or in the PAPAGENO Windows-Administrator in the menu "process" all processes that run on the computer are displayed. There you can start or stop processes via buttons.

ATTENTION: Be shure to use the commands `l_stopfax`, `l_startfax` and `t_shutdown` only in case of exception.

During the installation of PAPAGENO the service "fax server" is configured so in such a way that it is started and stopped automatically with Windows[®].

CMD-line Commands (Software Interfaces)

With PAPAGENO you can also use the CMD-line commands. With these commands you can control all actions that can also be executed via PAPAGENO interfaces (user and printer clients, administration program).

With the command `a_find_do` you can, furthermore, record charges for each user separately, find documents and initiate actions (delete, forward, send documents, etc.)

4. How to install a User-friendly Administration Program

In addition to the ASCII interface (comfax-adm) you can:


- install the graphical user interface **Windows-Administrator** on an Windows® system.
- use the Web-Administrator via a Web browser.
This gives you computer independent access via HTML technology.
Requirement: The Windows-Administrator has to be installed on this computer.

To install the Windows-Administrator

- ▶ Insert the PAPAGENO installation CD.
- ▶ Start the installation by opening `Software > Install` in the Control Panel.
- ▶ Click `Search` and change to the directory `VB Admin/English`.
- ▶ Select `Setup` and click the button `Open`.
- ▶ Confirm with `Complete`.

The administration program will be installed.

You can launch the program by clicking the desktop icon „Link to papageno.exe“.



5. How to Install a Single PAPAGENO Server

Requirement: A PAPAGENO basic installation with the OMEGA server.

Reminder:

You can install ALPHA, THETA and PI servers separately on different computers.

- ALPHA servers are responsible for user and document management.
An additional ALPHA server should be installed if users and documents are to be managed separately (not on the fax computer).
- Install a THETA server on each computer with a connected/mounted device (ISDN card, modem, PAPAGENO communication system).
- Install a PI server on each computer connected to a printer.

The procedure for server installation is exactly the same as for the main installation

Under "Server components" select only the server you wish to install (only ALPHA, THETA or PI server).

- ▶ Deactivate the other server components.
- ▶ Enter the host name (alias name) of the computer on which the OMEGA server is installed where the main installation has been carried out).

What is included with the installation of a PAPAGENO server?

- PAPAGENO drivers for devices
- Reserved user names
- comfax-adm administration program
- PAPAGENO commands
- CMD-line commands (software interfaces)

6. How to Install a PAPAGENO Mail Gateway

PAPAGENO can be connected to your mail system via a mail gateway (see above Part A, Chapter 6., „How to Connect PAPAGENO to your Mail System”, page 25) .

The PAPAGENO **SMTP Gateway** is installed with the PAPAGENO main installation.

If the gateway should run on a different computer:

- ▶ Install PAPAGENO on that computer and deactivate all server components (ALPHA, THETA and PI) during the installation (see 5., „How to Install a Single PAPAGENO Server”, page 54).

If a PAPAGENO mail gateway is already in use:

- ▶ Install the **newest upgrade**. Otherwise errors may occur!

7. Starting and Stopping the PAPAGENO Servers

Select Start > Settings > Control Panel > System > Administration Tools
> Fax servers

Normally the PAPAGENO fax server is started automatically when Windows® is started and stopped when Windows® is shut down.

8. How to Install an Update Version

Within one network an identical PAPAGENO version must be installed on all PAPAGENO computers .

The accounts and documents remain unchanged during an update.

PLEASE NOTE:

Version 5.0 servers or higher are not compatible with server processes for earlier versions!
If PAPAGENO servers are installed within a PAPAGENO cell on distributed computers, an update to version 5.0 must be made on all these computers.

First of all update the fax server, then all other computers with PAPAGENO server processes.

How to install an update

The procedure for installing an update is exactly the same as for a first-time installation.

- ▶ Select the directory in which „the old“ PAPAGENO version is installed.
- ▶ Answer “yes” to the questions whether the server computer and RPC port mapper should be shut down.
- ▶ Select the server components (all or only certain PAPAGENO server processes) you wish to install.

How to Install an ALPHA Server Update

To update an ALPHA Server do the same as with a normal update; just be sure to anywhere enter “ALPHA Server” when asked for server components.

9. How to Handle a Large Number of Documents

If faxes and voice mails **are stored on the mail server** (see „Retrival of the Faxes, Voice Mails AND Mails“, page 33) you do **not** need to regard this page.

During installation, 16 subdirectories are created for each ALPHA server in the directories `e` (Incoming), `p` (Desktop) and `s` (Outgoing). In order to avoid difficulties caused by large numbers of documents in one directory.

For large installations it is recommended to even increase the number of subdirectories.

16 directories are recommended for small and medium-sized, 256 for large installations.

The creation of subdirectories is recommended when upgrading from comFAX 4.0 or earlier.

To Increase the Number of Subdirectories ...

via the ALPHA configuration variables `DIRBUCKETE`, `DIRBUCKETP` and `DIRBUCKETE`.

If you have a large number of documents this may take an hour or more!
PAPAGENO users will **not** be able to continue working during this time.

How to Use the Variables

- ▶ Log in as administrator to the ALPHA computer on which you wish to create the subdirectories.
- ▶ Start the ALPHA server by entering `l_startserver alpha`
- ▶ Open the `Start` menu then choose `Settings > System`. Open `System attributes` and select `Environment`.
- ▶ For user `PAPAGENO` set for the environmental variable `SETUSER` to `FAXADM`
- ▶ Restart Windows®.
- ▶ In the MS-DOS command line enter `a_put_usrconf` *variable name* and *value*.

Example: `a_put_usrconf DIRBUCKETE 16`

Values must be positive integer up to 4096.

- ▶ Stop the ALPHA server with the command `l_stopserver alpha` and then restart it with `l_startserver alpha`

Documents will be assigned via links to the according subdirectories on the basis of their document number. Filed signatures and desktop documents which are currently being worked on will be stored in dedicated directories (`signature` and `scratch`). Once this has been completed, the original directory will be replaced by the converted directory. The original directory will be renamed with the extension `_old`. The variables then will be deleted to prevent subdirectories being created all over again when the ALPHA server is started the next time.

Once you are sure that the conversion has been successful:

- ▶ Delete the directory with the ending `_old`.

10. How to Deinstall PAPAGENO

- Insert the PAPAGENO CD.
- In the Control Panel select Software.
- Select the PAPAGENO software and click on Add/Remove.

11. How to Install Devices

If you have not yet installed the devices to receive or send faxes you have to install and configure them now.

Installing ISDN Cards

- ▶ Install the ISDN card (s) on a Windows® computer.
- ▶ Make sure that a THETA server is running on each computer with an ISDN card.

Connecting the PAPAGENO Device Computer to the Network

If a ready-configured PAPAGENO computer is being used as a device:

- ▶ Assign an IP-address to this computer and connect it to the network.
- ▶ Register the OMEGA host under `$FAXSERVER/etc/config`.
- ▶ Enter the OMEGA host with its corresponding IP-address in the host table of the PAPAGENO computer.
- ▶ Enter the PAPAGENO computer with the corresponding IP-address in the host table of the OMEGA computer.

After this:

- Publish the OMEGA server to the THETA server (register it as a new server in the administration program. See also: Part C, 15. „How to Forward Faxes Free of Charge to a Remote PAPAGENO Installation“, page 121)
- Register PAPAGENO as a device in the administration program.

Setting Up Modems

- ▶ Install them.
- ▶ Make sure that a THETA server is running on each computer connected to a modem.

12. How to Install FAX Clients

If users want to work only with faxes, we provide several FAX clients:

- **comFAX/Win**: fax client under Windows®: runs on 32 Bit Windows® versions and dedicated 64 Bit versions.
- **comFAX/ X Window**: runs under Unix with an X Window interface
- **comFAX/ASCII**: ASCII interface for Unix and Windows® users. (Faxes can be displayed only in a limited way!)

Installation of the fax clients

comFAX/Win

The installation files can be found on the CD in the directory `support_for_old_Versions\Fax-Client` respectively on our website (`Download - PAPAGENO - Software - User Clients`).

comFAX/ X Window

comFAX/ X Window is installed together with the basic Unix installation of PAPAGENO or PAPAGENO servers.

comFAX/X Window can be started in a Unix shell **with the Unix ID of a user. X Window must exist.**

comFAX/ASCII

comFAX/ASCII is installed with the basic installation of PAPAGENO or PAPAGENO servers.

comFAX/ASCII can be started at shell level or at the MS-DOS command line.



B2. Installing PAPAGENO on Linux/Unix

1. Prior to Installation	65
Verifying the RPC Services	66
Making Entries in the <code>/etc/hosts</code>	66
How to Define an Alias Name	66
2. PAPAGENO is Easy to Install	67
3. After Installation	69
Creating a Start and Stop Script:	69
Creating a Start and Stop Script:	69
4. How to Establish a Sandbox	71
5. Installed With PAPAGENO are:	72
Reserved User Names.	72
The <code>comfaxdefault</code> File.	72
<code>comfax-adm</code> Administration Program.	73
PAPAGENO Commands	73
Printer Clients.	74
CMD Line Commands (Software Interfaces)	74
6. How to Install an Update Version	75
How to Install an Update	75
How to Install an ALPHA Server Update	75

7. Large Number of Documents	76
To Increase the Number of subdirectories	76
How to Use the Variables	76
8. Starting and Stopping the PAPAGENO Servers	77
9. Deinstallation of PAPAGENO	78
10. How to Install a Single PAPAGENO Server	79
11. How to Install Devices	81
Installing ISDN Cards	81
Connecting the PAPAGENO Device Computer to the Network	82
Setting Up Modems	82
12. Providing Access to the Mail Server	83
13. How to Install FAX Clients	84

1. Prior to Installation ...

... pay attention to the following **requirements**:

- A Connection to the telephone network exists
PAPAGENO have **access the public telephone network** via one or more PRI or BRI connections and CAPI. This link can be realized either by a TC system or a telephone provider.
- A **CAPI interface** on the PAPAGENO device computer (Windows® computer) exists.
- A mail server is installed and configured.

If you plan a configuration with an **IMAP and LDAP** connection between the PAPAGENO device and the mail server:

- ▶ First make sure that the LDAP and IMAP4 services are set up on your mail server.

PLEASE NOTE: Prior to Version 5.2, PAPAGENO was called comFAX
comFAX still appears frequently in internal names and commands.

How to set up the Unix user `comfax` and the installation directory

- ▶ With Bourne Shell (bash) or Korn Shell (ksh) create the login shell for the user `comfax` on the computer on which PAPAGENO will be installed.
If the software is going to be installed in the HOME directory of the user `comfax` the creation of a subdirectory (e. g. `faxroot`) is recommended. This will distinguish the `bin` directory of the user from the `bin` directory of the PAPAGENO directory.
- ▶ Create an installation directory in which PAPAGENO is to be installed. This directory must belong to the user `comfax`.
- ▶ Assign the rights `rwX r-X r-X` to the user `comfax` for this directory.

Verifying the RPC Services

RPC services (Remote Procedure Calls) must be available for the installation of PAPAGENO. These services can be found either in TCP/IP or in the NFS package of the operating system.

To verify that the network services are activated in your system:

- ▶ Enter the commands

```
ping localhost
and
ping `uname -n`
```

If these commands are executed correctly the file `/etc/hosts` contains a correct entry for the computer to be installed.

The output of the following two commands must be identical. In addition to other services the port mapper service is generally displayed in SV R3-Unix systems and the “rpcbind” service in SV R4-Unix systems.

- ▶ Enter the command
`rpcinfo -p localhost.`
- ▶ Enter the command
`rpcinfo -p `uname -n`.`

The availability of RPC services is also verified at the start of the PAPAGENO installation.

Making Entries in the `/etc/hosts`

The `/etc/hosts` file must contain the following entry for “local host”:

```
127.0.0.1 localhost
```

The `/etc/hosts` file must contain the correct IP address with the computer name.

- ▶ Check the entries.

How to Define an Alias Name

- ▶ In the `/etc/hosts` file assign an alias name to the computer on which the OMEGA server is going to run.

It is possible that a name server (DNS) managing the host names of all computers in the network is being used. In this case the name entered in the local `/etc/hosts` file is not applicable. Refer to your network administrator on how to proceed.

2. PAPAGENO is Easy to Install

- ▶ Log in as user `comfax`.
- ▶ In our Website open via Downloads PAPAGENO - Software packages - PAPAGENO-Server Version 5.9 the PAPAGENO server versions of the several operating systems.
- ▶ Download the desired PAPAGENO operating system version.
or
- ▶ Mount the CD device
- ▶ Change to the directory in which PAPAGENO shall be installed.
- ▶ Unzip the software with command `tar -xvf filename` .
filename consists of the path, the name of the operating system and the PAPAGENO version.
Example:
`tar xvf/cdrom/server/AIX3.2-4`

PAPAGENO directories and files will be copied into the installation directory.

To start the installation:

- ▶ In the installation directory execute the command `etc/install_fax`.

Usually you accept all the default settings (left column, bold) with the button `Next` :

Setting options	Meaning	Input
1 Deutsch 2 English 3 Francais	Installation language	Enter a number
b f q	<u>B</u> asic installation <u>E</u> urther installations <u>A</u> bort	Enter a letter

- ▶ Enter the **alias name** for the server computer.

-
- When installing from CD, enter the **licence key**.

Germany Other countries	Country in which PAPAGENO is being used, can be changed later	Enter a number
1 Deutsch 2 English 3 Francais	Language for user interfaces, can be changed later	Enter number
8859 Charset Other character sets	Default character set, can be changed later	y or n

Complete the installation protocol. It will be sent to VIPcom as a fax after installation

What happens during installation?

During installation the database is generated and filled.

Entries for the environment variable `FAXROOT` and for invoking the file `comfaxdefault` are added to the `.profile` file.

The LAMBDA, NUE, OMEGA and ALPHA servers are started.

The installation protocol is generated and a fax job to VIPcom is generated.

User client(s) (`comfax-asc` and `comfax-x`) are set up.

Subsequently the basic installation is completed.

Finishing the installation

- Log off.
- Log in again as user `comfax`.
- Enter the command `runcomfax`.

For further information on `runcomfax` see also below „PAPAGENO Commands”, page 73.

The other servers will be started.

3. After Installation ...

... configure the PAPAGENO server processes to automatically start and stop.

To start the PAPAGENO server each time the computer is started and to stop it when the computer is shut down is important because the database must be opened and closed properly. Otherwise data loss may occur!

Upon installation a start/stop script is created which ensures that the server is stopped automatically during shutdown and restarted when each time the operating system is started.

Creating a Start and Stop Script:

- ▶ Login as user `comfax`.
- ▶ Execute the command `$FAXROOT/etc/make_rc`.

The file `comfax.rc` will be created.

`comfax.rc` activates the automatically start and stop

Setting up Automatic Start and Stop:

Configuring how to automatically start and stop the PAPAGENO servers depends on your operating system.

Linux Debian, Ubuntu

- ▶ Kopieren Sie die Datei `$FAXROOT/etc/comfax.rc` in das Verzeichnis `/etc/init.d`
- ▶ Geben Sie das Kommando `update_rc.d comfax.rc defaults` ein.

RedHat, SuSE, Fedora

- ▶ Kopieren Sie die Datei `$FAXROOT/etc/comfax.rc` in das Verzeichnis `/etc/init.d`
- ▶ Geben Sie das Kommando `checkkconfig --add comfax.rc` ein.

Here is a suggestion for **most Unix operating systems**:

- ▶ Copy the file `/tmp/rc.comfax` to the directory `/etc/rc2.d` under the name: `S99comfax` and to the directory `/etc/rc0.d` under the name: `K01comfax`.

In `S99comfax` and in `K01comfax` you will find the following lines:

```
su - comfax -c stopcomfax
su - comfax -c runcomfax
```

`stopcomfax` is the command for stopping,
`runcomfax` the command for starting the server.

PAPAGENO is based on the communication mechanisms of RPC. For this reason the script for starting the servers cannot be executed until TCP/IP and the RPC services have been successfully launched. The script for stopping the server must be executed before closing TCP/IP and RPC. Otherwise the PAPAGENO server processes will no longer be accessible.

Attention! Make sure that the `.profile` file of the user `PAPAGENO` is not configured for interactive query (e.g. query of terminal type, etc.). This would prevent automatic starting and stopping of the PAPAGENO servers.

4. How to Establish a Sandbox

Under Linux you can establish a sandbox. In this isolated area the PAPAGENO SMTP gateway and the printer client faxpspr will run. The sandbox provides read-only access for the most important areas of the operating system. Only the directories `FAXROOT`, `tmp` and `var/tmp` have full access rights.

Establishing the Sandbox

- ▶ Create the start script `comfax.rc`
(see above „Creating a Start and Stop Script:“, page 69”).
- ▶ Assign executing rights to `comfax.rc`.
- ▶ Login as `root`.
- ▶ Establish `comfax.rc` as start script (see above „Setting up Automatic Start and Stop:“, page 69)
Every time PAPAGENO is started as `root` the sandbox will be built.
(If the start script runs as user `comfax` no sandbox will be created).

How to check that processes are running in the sandbox

- ▶ Look to the `gateway` and `daemon` logbooks .
- ▶ In a shell enter the command `faxpspr -debug`.

To start PAPAGENO without sandbox:

- ▶ Login as system user `comfax`.
- ▶ Start PAPAGENO via the command `runfax`.

5. Installed With PAPAGENO are:

- **All of the PAPAGENO server processes**
ALPHA, OMEGA, THETA, PI, LAMBDA, NUE, GAMMA
- **PAPAGENO drivers for devices**
- **The PAPAGENO SMTP Gateway**
It is unlocked by entering the license key and can be activated by a configuration variable (see Manual „PAPAGENO-SMTP-Gateway“)

Reserved User Names

User name	Description
User comfax	comfax is a sample user in PAPAGENO
System administrator FAXADM	The user FAXADM has access to the documents and telephone books of all users handled by an ALPHA server. This user should be protected by a dedicated password.
user .winpr	The user .winpr is the owner of all documents spooled to the com-faxps or comfaxpr printer via the THETA server. As the user .winpr is preceded with a “dot”, this name does not appear in the PAPAGENO user list.
System administrator .routing	The user .routing is important for the processing of least-cost rou-ting. As the user .routing is preceded with a “dot”, this user does not appear in the PAPAGENO user list.

The comfaxdefault File

The standard PAPAGENO environment is set in this file. The names of the OMEGA and ALPHA computers as well as the default language and character set for PAPAGENO interfaces are entered here. This information is set during installation.

You can change the language and character set in this file and set each according to user and/or device. You can also set the OMEGA host according to users.

The file `comfaxdefault` will be processed each time PAPAGENO is launched.

comfax-adm Administration Program

Most of the administration procedures can be operated via the **ASCII interface** of this program under Unix, Linux and Windows®.

The graphical interfaces of the administration program (PAPAGENO Windows-Administrator and Web-Administrator) must be installed separately.

PAPAGENO Commands

The following contains a description of the most important PAPAGENO commands:

Command	Description
l_startserver alpha/ runalpha l_stopserver alpha	Starts respectively stops the ALPHA server on the local computer. All other servers can be started in the same way (e. g. l_startserver omega)
l_startserver <i>server</i> / runserver l_stopserver <i>server</i>	<i>server</i> means the server names (omega, gamma, lambda, nue, pi, etc.). Starts respectively stops the named server on the local computer. Attention: l_stopserver theta does not exist . Use t_shutdown resp. stopdrivers instead (see below).
t_shutdown/ stopdrivers	Stops the THETA-Server. The current job on the corresponding device will be completed first!. When all drivers have been stopped, the THETA server will shut down . The completion of a current send or receive job will be finished currently but may take some time. Check this with the command l_ps when the shutdown has been finished.
l_startfax/ runfax	Starts all configurable server processes on the local computer. To use l_startfax the LAMBDA server has to run first.
l_stopfax/ stopfax	Stops all server processes on the local computer - except for the LAMBDA server.
l_startdrivers	Starts all locally accessible drivers. The THETA server must be started separately with the command l_startserver theta. If the other servers are not accessible documents can be received this way. These documents will be saved locally until the responsible ALPHA server is accessible again.
l_startdriver <i>driver</i> l_stopdriver <i>driver</i>	Starts or stops the named driver. <i>driver</i> is the name by which the fax or telex driver equipment has been registered in the administration program. The driver gd-capidrv is finished automatically as soon as all lines are "dead"..
l_stopgateways	Stops all local gateway processes

Command	Description
<code>l_startdaemon</code> <i>deamon</i> <code>l_stopdaemon</code> <i>daemon</i>	Starts/stops the according daemon process.
<code>l_startgateway</code> <i>gateway</i> <code>l_stopgateway</code> <i>gateway</i>	Starts/stops the according gateway process.

In the PAPAGENO-Web-Administrator or in the PAPAGENO Windows-Administrator in the menu "process" all processes that run on the computer are displayed. There you can start or stop processes via buttons.

Printer Clients

The PAPAGENO printer clients `comfaxps`, `comfaxpr` and `comfaxpspr` enable the sending of faxes directly from an application. ASCII documents can be generated with `comfaxps`, postscript documents with `comfaxpr`. `comfaxpspr` automatically differs between ASCII and postscript. `comfaxps` permits documents to be sent from any Unix application.

A number of **options** exist for printer clients, e.g. exact time slots (night rate), etc.

Addresses, time slots, text formatting, etc. can be specified in the document itself by **internal control characters**.

CMD Line Commands (Software Interfaces)

With the installation of PAPAGENO you can also use the CMD line. With these commands you can control all actions that can also be executed via PAPAGENO interfaces (user and printer clients, administration program).

With the command `a_find_do` you can, furthermore, record sending charges for each user separately, to find documents and to initiate actions (delete, forward, send documents, etc.)

comFAX Clients

The PAPAGENO user can apply the comFAX ASCII (`comfax-asc`) and X Window (`comfax-x`) clients for fax management.

Both clients can be activated/invoked immediately after the PAPAGENO installation.

6. How to Install an Update Version

Within one network an identical PAPAGENO version must be installed on all PAPAGENO computers .

The user accounts and documents remain unchanged during an update.

PLEASE NOTE:

Version 5.0 servers or higher are not compatible with server processes for earlier versions!
If PAPAGENO servers are installed within a PAPAGENO cell on distributed computers, an update to version 5.0 must be made on all these computers.

First of all update the fax server, then all other computers with PAPAGENO server processes.

How to Install an Update

- ▶ With the command `stopcomfax` stop PAPAGENO on all systems.
- ▶ With the command `t_get_kzg` verify that the device driver has been stopped as well.
If yes you will receive an error message (e.g. `RPC not registered`).
- ▶ Log in as user `comfax` and change to the installation directory.
- ▶ Load the software.
- ▶ Enter the command `update_comfax` .
- ▶ When the installation is complete, enter `runcomfax`.

How to Install an ALPHA Server Update

To update an ALPHA Server do the same as with a normal update; just be sure to anywhere enter "ALPHA Server" when asked for server components.

7. Large Number of Documents

If faxes and voice mails **are stored on the mail server** (see „Retrival of the Faxes, Voice Mails AND Mails“, page 33) you do **not** need to regard this page.

During installation, 16 subdirectories are created for each ALPHA server in the directories `i` (Incoming), `p` (Desktop) and `s` (Outgoing). In order to avoid difficulties caused by large numbers of documents in one directory.

For large installations it is recommended to even increase the number of subdirectories.

16 directories are recommended for small and medium-sized, 256 for large installations.

The creation of subdirectories is recommended when upgrading from comFAX 4.0 or earlier.

To Increase the Number of subdirectories ...

via the ALPHA configuration variables `DIRBUCKETE`, `DIRBUCKETP` and `DIRBUCKETE`.

If you have a large number of documents this may take an hour or more!
PAPAGENO users will **not** be able to continue working during this time.

How to Use the Variables

- ▶ Log in as user `comFAX` to the ALPHA computer on which you wish to create the subdirectories.
- ▶ Start the according ALPHA server by entering `runalpha`.
- ▶ Set the environment variable `SETUSER` to `FAXADM`
- ▶ In a Unix shell enter `a_put_usrconf variable value`.

Example: `a_put_usrconf DIRBUCKETE 16`

Values must be positive integer up to 4096.

- ▶ Stop the ALPHA server with the command `l_stopserver alpha` and then restart it with `l_startserver alpha` or `runalpha`.

Documents will be assigned via links to the according subdirectories on the basis of their document numbers. Filed signatures and desktop documents which are currently being worked on will be stored in dedicated directories (`signature` and `scratch`). Once this has been completed, the original directory will be replaced by the converted directory. The original directory will be renamed with the extension `_old`. The variables then will be deleted to prevent subdirectories being created all over again when the ALPHA server is started the next time.

Once you are sure that the conversion has been successful:

- ▶ Delete the directory with the ending `_old`.

8. Starting and Stopping the PAPAGENO Servers

- ▶ To start server enter `runfax` to stop it enter `stopfax`.

If automatic starting/stopping has been configured the fax server is started/stopped during start/shutdown of the operating system.

9. Deinstallation of PAPAGENO

- Delete the complete `$FAXROOT` directory including any subdirectories.
- Delete the entries for PAPAGENO in the `.profile` file.

10. How to Install a Single PAPAGENO Server

Requirement: A PAPAGENO basic installation with the OMEGA server.

Reminder:

You can install ALPHA, THETA and PI servers separately on different computers.

- ALPHA servers are responsible for user and document management. An additional ALPHA server should be installed if users and documents are to be managed separately (not on the fax computer).
- Install a THETA server on each computer with a connected/mounted device (ISDN card, modem).
- Install a PI server on each computer connected to a printer.
- Printer clients should be installed separately to relieve the load on the other PAPAGENO server systems. (The CPU gets strained when fax documents are generated.)

The procedure for server installation is exactly the same as for the main installation

- ▶ Archive the preliminaries (create the user `comfax`, verify RPC services, check entries in the file `etc/hosts`).
- ▶ Use the command `rlogin` to verify if the computer on which the OMEGA server is installed can be accessed in the network.
- ▶ Log in as user `comfax`.
- ▶ Load the software.
- ▶ Change to the directory in which the software is installed.
- ▶ Execute `etc/install_fax`.
- ▶ Select `w` for "Installation on further computers".
- ▶ Enter the host name (alias name) of the computer on which the OMEGA server is installed (i.e. the main installation has been carried out).
- ▶ Select the server type you wish to install (either ALPHA or THETA or PI).
- ▶ Log out and in again as user `comfax`.
- ▶ Enter the command `runcomfax`.
- ▶ Configure automatic starting and stopping.

How to install printer clients only:

- ▶ Proceed exactly as with the installation of individual servers (make preparations, load software, start installation, select `w`, indicate alias name for OMEGA host).
- ▶ Select **no** PAPAGENO server.
- ▶ Answer `Yes` to the question whether you wish to use another computer's ALPHA, THETA and PI server.

What is included with the installation of a PAPAGENO server?

- PAPAGENO drivers for devices
- Reserved user names
- `comfax-adm` administration program
- Printer clients
- PAPAGENO commands
- User clients (`comfax-asc` and possibly `comfax-x`)
- CMD line commands (software interfaces)

11. How to Install Devices

If you have not yet installed the devices to receive or send faxes you have to install and configure them now.

Installing ISDN Cards

- ▶ Install the ISDN card (s) on a Windows® computer.
- ▶ Make sure that a THETA server is running on each computer with an ISDN card.

Installing Dialogic Diva Server Card under Linux

To set up a Dialogic (former Eicon) Diva Server card under Linux RedHAT or SuSe 8.1 you have to install the latest software version and then configure the card.

Requirement

The card is built in.

Download RPM package

- ▶ On the Dialogic website (www.dialogic.com) download the current installation RPM package for the card and the Linux kernel.

Installing the RPM package

- ▶ Change to the RPM package directory.
- ▶ In a command line enter

```
rpm -U packagename
```

packagename is the name of the RPM package.

Configuring the card

- ▶ Change to the `/usr/lib/eicon/divas` directory.
- ▶ Activate the `config` file and configure the card.

Delivering capi 20

Change the rights so that only PAPAGENO can use the capi 20.

- ▶ In a command line enter

```
chown comfax /dev/capi20
```
- ▶ Enter:

```
chmod 600 capi20.
```

Connecting the PAPAGENO Device Computer to the Network

If a ready-configured PAPAGENO computer is being used as a device:

- ▶ Assign an IP-address to this computer and connect it to the network.
- ▶ Register the OMEGA host under `$FAXSERVER/etc/config`.
- ▶ Enter the OMEGA host with its corresponding IP-address in the host table of the PAPAGENO computer.
- ▶ Enter the PAPAGENO computer with the corresponding IP-address in the host table of the OMEGA computer.

After this

- Publish the OMEGA server to the THETA server (register it as a new server in the administration program. See also: Part C, „How to Forward Faxes Free of Charge to a Remote PAPAGENO Installation“, page 121)
- Register PAPAGENO as a device in the administration program.

Setting Up Modems

- ▶ Install them.
- ▶ Make sure that a THETA server is running on each computer connected to a modem.

12. Providing Access to the Mail Server

In order to provide a connection between PAPAGENO and the mail server you can install

- either **MAPI connectors** on each user computer
- or
- a **mail gateway**.

If a mail gateway is going to be applied:

You have to enable the gateway and set some variables. See „PAPAGENO SMTP Gateway“ manual. The PAPAGENO **SMTP Gateway** is installed with the PAPAGENO main installation.

If the gateway should run on a different computer:

- ▶ Install PAPAGENO on that computer and deactivate all server components (ALPHA, THETA and PI) during the installation (see 10. „How to Install a Single PAPAGENO Server“, Seite 79).

If an LDAP directory server is in use, you have to register all fax and voice mail users in the directory server.

If a PAPAGENO mail gateway is in use:

- ▶ Install the **newest upgrade**. Otherwise errors may occur!

Configuring Telephone Access to Messages

If a mail gateway is used, all faxes and voicemails are stored in the mailserver together with the emails. They are erased from the PAPAGENO database. In this case users **cannot access** to their messages via phone.

For this problem there are two solutions:

- Enter that all incoming messages are stored in the mail server **and** in PAPAGENO .
(Then faxes and voice mails can be accessed via phone)
- Access to the mail server database via **IMAP4**.
(According to the faxes and voicemails even the emails can be accessed)

NOTE: In any case users must have numeric passwords to authorize themselves for the telephone access („pincode“)

If PAPAGENO MAPI connectors are going to be used:

- ▶ Install a MAPI connector on each user's computer.
See manual „PAPAGENO MAPI Connector“.

13. How to Install FAX Clients

If users want to work only with faxes, we provide several FAX clients:

- **comFAX/Win**: fax client under Windows®: runs on 32 Bit Windows® versions and dedicated 64 Bit versions.
- **comFAX/ X Window** runs under Unix with an X Window interface
- **comFAX/ASCII**: ASCII interface for Unix and Windows® users. (Faxes can be displayed only in a limited way!)

Installation of the fax clients

comFAX/Win

The installation files can be found on the CD in the directory
`support_for_old_Versions\FaxClient` respectively on our website (Download - PAPAGENO - Software - User Clients).

comFAX/ X Window

comFAX/ X Window is installed together with the basic Unix installation of PAPAGENO or PAPAGENO servers.

comFAX/X Window can be started in a Unix shell with the Unix ID of a user. X Window must exist.

comFAX/ASCII

comFAX/ASCII is installed with the basic installation of PAPAGENO or PAPAGENO servers.

comFAX/ASCII can be started at shell level or at the MS-DOS command line.



C. Administer PAPAGENO

1. PAPAGENO Administrator	87
There are Three Different Administration Programs	87
Items Entered Via the Administration Program	88
Differences in Program Structure	88
Starting the PAPAGENO Windows-Administrator	89
Working with the PAPAGENO Windows-Administrator	90
2. Assigning an Administrator Password	91
3. Registering the PAPAGENO Servers	92
Make Adjustments for Dispatching Jobs if Necessary	93
Increase the Debug Level if Necessary	94
Starting and Stopping Server Processes Via the Administrator Program	95
4. Registering Users	96
How to Register a New User	97
How to Enter User's Fax Send Properties	98
How to Appoint a Substitute	99
How to Enter Different User Notification Types	101
How to Define Background Paper for the User's Faxes	102
5. Registering Devices and Device Drivers	103

6. Setting Up Services in PAPAGENO	104
How Many B Channels are Available?	105
7. Registering ISDN Cards	106
How to Send Faxes Including the CPI	108
How to Enter Parameters for the Inbound Routing	109
How to Use Voicemail	110
How to Calculate Charges	111
8. Registering a PAPAGENO Communication Server	112
9. Registering a Modem	113
If the modem is voicemail-capable:	114
If you want to enter driver-dependent parameters:	114
10. Enter at Least One Distribution Rule	115
How to Change Distribution Rule r1:	115
11. PAPAGENO is now ready to use!	116
12. How to Deliver an Incoming Message to Several Users	117
13. Entering Additional Distribution Rules	118
14. If Faxes Are to be Printed	120
15. How to Forward Faxes Free of Charge to a Remote PAPAGENO Installation	121
16. How to Use Fax Number Mapping or Call by Call	122
17. Storing Messages in PAPAGENO	124

1. PAPAGENO Administrator

There are Three Different Administration Programs

- **comfax-adm**
- **PAPAGENO Windows-Administrator**
- **PAPAGENO Web-Administrator**

The **setting options are the same in all three administration programs**.
The interfaces can, however, be applied in **various environments**.

comfax-adm	Windows-Administrator	Web-Administrator
ASCII interface	Windows [®] interface	HTML pages
Runs on any Unix, Linux or Windows[®] system in the network (via Telnet).	Runs on any Windows[®] computer with a network link to the PAPAGENO system.	Can be executed via web browser on every computer in the network Enables computer-independent access via HTML technology.
Automatically included in the basic PAPAGENO installation Unified messaging services can not be setup!	Must be installed on a Windows [®] system.	Must be installed on a Windows system with Microsoft[®] Internet Information Server (IIS) . PAPAGENO Windows-Administrator must be installed on the same computer.

PAPAGENO Windows-Administrator and PAPAGENO Web-Administrator offer **additional features** compared to comfax-adm. (e.g. registration of user substitutes and setting actions, deleting gateway users from the database, voice settings for voicemails).

The following chapters describe the Administration with the PAPAGENO Windows-Administrator interface.

Items Entered Via the Administration Program

In order to make PAPAGENO operative:

- Register the server on which the PAPAGENO server processes are installed
- Enter the user data of all PAPAGENO users or the Gateway users
- Install the drivers for all **devices** and **services** that being used
- Enter at least one **distribution rule**
via the **administration program**.

In addition, you can:

- Set up **user groups** to which incoming faxes are to be on-routed
- Set up further **distribution rules** for incoming faxes
- Register **printers** which are used for printing faxes
- **ALPHA servers** on PAPAGENO installations of another cell ("remote ALPHA server")
- Replace starting numbers of specific fax numbers by other numbers (**number substitution**).
- **Poll documents** for passive polling
- Set **system parameters**, e.g. for sending copies of all incoming documents to a specific user.

Differences in Program Structure

The following differences in program structure exist in the administration programs:

PAPAGENO **Windows-Administrator** and PAPAGENO **Web-Administrator**:

In case of a distributed installation you first have to register all computers on which the PAPAGENO servers are installed. Users (ALPHA servers installed), devices (THETA servers installed) or PAPAGENO printers (PI servers installed) must be registered for these computers thereafter.

When registering a user, a device or a printer in **comfax-adm** you specify which server computer to use.


Only remote ALPHA server computers have to be registered here.

Attributes of ALPHA servers are specified in "System Parameters".


Starting the PAPAGENO Windows-Administrator

The PAPAGENO Windows-Administrator can be executed on any Windows® system within the PAPAGENO network.

- ▶ Double-click the PAPAGENO Windows-Administrator icon (Link to `papageno.exe`) on the desktop to open the login window..



- ▶ In the `Host Name` field enter the name of the computer on which the OMEGA server is installed and confirm.
- ▶ The main window of the administration program will open.



Working with the PAPAGENO Windows-Administrator

The individual folders are listed on the left. Click on a folder to view the sub-folders on the next level or their contents in the list box on the right.

The folder `Servers` contains the sub-folders `Processes` and `Events` and if entered yet, the sub-folders `Users`, `Printers` and `Devices`.

Adding entries to a folder

- ▶ Click in the left-hand list box with the right mouse button on the appropriate folder and select `New...`

or:

- ▶ Highlight the folder and then select the option `New...` in the menu `File`

Displaying entries

- ▶ Double-clicking on an entry will open a window in which you can view and change data.

Conventions

For all devices, printers, users, user groups, distribution rules and server configurations the first box must always contain a unique short term corresponding to the key field of a database.

The short term must not be longer than 10 characters and must not contain spaces or special characters. It should start with a letter. Once the entry is confirmed, it cannot be changed.

Each short term has a comment box for a more detailed description (30 characters, spaces and special characters allowed).

Deleting entries

To delete an entry from the right-hand list box:

- ▶ Highlight the entry and press the `DEL` key.


Changing entries

- ▶ In the left-hand list box click the right mouse button on the appropriate folder and select `Properties...`
or:
highlight the folder `Administrator` and select the option `Properties...` in the menu `File`.

2. Assigning an Administrator Password

While the administration program can be accessed by any user the password ensures that no changes can be made by an unauthorized person!

- ▶ In the main administration program window highlight the folder `Administrator`.
- ▶ Open the menu `File - Properties...`
- ▶ In the window `Administrator Details` click `Change Password...` to open the `Change Password` window.



- ▶ Enter the password in the `New Password` edit box.
- ▶ Re-enter the password in the `Confirm New Password` box.
Your entry will not be readable. The characters will be replaced by asterisks.
- ▶ Close the window with `OK`
If the password entries concur the new password will be saved and must be entered next time you log in.

NOTE: If you forget the password for the PAPAGENO administrator, you will not be able to access the administrator program.

In this case, PAPAGENO must be re-installed.


The administrator password can be changed at any time in the `Change Password` window. The new password is valid as soon as it has been entered correctly.

3. Registering the PAPAGENO Servers

In the administration program the **servers** (networked computers, on which PAPAGENO server processes are installed).have to be registered.

For each server you can, for instance, determine whether PAPAGENO users shall use it as an ALPHA server. You can also determine whether devices (modems or ISDN cards) or printers are to be connected to the computer. If devices are connected, a THETA server must be installed, if printers are connected, a PI server must be installed.

- ▶ In the main administration program window, highlight the folder `Server`.
- ▶ In the menu `File` click `New ...` to open the window `Server Details`



General file card

Host Name	Short term, maximum 10 characters, no spaces or special characters. First character should be alphanumeric. After confirmation this entry cannot be changed anymore. Confirm with <code>Return</code> .
User Server	Activate if documents and the environment of users shall be stored on this server computer. (ALPHA-Server must be installed).
Device Server	Activate if devices are connected to or installed on this server computer. (THETA-Server must be installed).
PrinterServer	Activate if a printer is connected to this server computer. (PI-Server must be installed).
Comment	Description (up to 30 characters)

At least one of the servers `User Server`, `Printer Server` or `Device Server` **has to be activated**.

If you activate one of the boxes `User Server`, `Printer Server` or `Device Server`, the corresponding sub-folder will be created once the server registration has been completed. Later on further users/devices/printers can be added in this sub-folder.

After activating the `User server` box, you can start the **ALPHA server**.


- ▶ On the computer for which you have registered the ALPHA server enter at the MS-DOS command prompt enter `l_startserver alpha`
or:
- ▶ start the ALPHA server via `System Control Panel - (Administration) - Services`
The ALPHA server will be started. The `Server Details` window will display `Online: Yes`.

Net Type	local or remote ALPHA server. Select the type of network to which the computer is connected. (<code>Local Area Network</code> for the local ALPHA server or <code>Wide Area Network</code> for a remote TCP/IP network). If the words <code>Online: Yes</code> are displayed in the box, the server is accessible.
-----------------	--

Make Adjustments for Dispatching Jobs if Necessary

The `Dispatch Properties` tab is activated only if the `user server` box is activated and the `Online - Yes` field is visible.


The "dispatcher" is the central job manager. It controls which jobs are dispatched and when, deactivates inactive logins, etc.



Serialize Same Number	Serialization should be activated. It ensures that several jobs to one destination are dispatched one after the other. If the serialization is deactivated sending jobs will be realized to parallel lines. Since receivers often have only one telephone line for reception the transmission jobs would handicap each other (busy line).
Dispatcher off	Deactivate the dispatcher. It is used for temporary system maintenance work only.
Dispatch Count	Use the arrow buttons in the Dispatch Limit box to select the number of dispatching jobs to be executed simultaneously by the ALPHA server. We recommend limiting jobs to 50 - 100.

Increase the Debug Level if Necessary

The `Debug` tab is active only if the `User Server` box is activated and the `Online: Yes` field is visible..



Debug Level	<p>The higher the debug level the more detailed the activities of the alpha server are logged. They are stored in the log directory <code>C:\FAXSERVER\alpha</code>. Debug levels vary from 1 – 10. Level 1 logs all standard messages, the highest level 10 logs all available messages. Attention! Logging on high level requires a lot of disk space! You cannot stop the recording of the server log file via the <code>Debug Level</code> field. This is only possible via the CMD line command <code>a_write_log</code>.</p>
--------------------	--

- Save your settings by clicking `OK`.

Starting and Stopping Server Processes Via the Administration Program

For each server computer you can stop and restart all running PAPAGENO processes.

How to stop or start ALL server processes:

- ▶ Click the right mouse button in the left list box on the server for which you wish to shut down all PAPAGENO processes.
- ▶ Select: `Stop` or `Start` in the menu.

How to stop or start a specific server process:

- ▶ In the left list box in the sub-menu of the server highlight `Processes`.
The server processes will display in the right list box.
- ▶ Highlight the server process which you wish to stop or start.
- ▶ Select: `Stop` or `Start` in the menu.

4. Registering Users

Depending on your configuration PAPAGENO users must be entered via the administration program in PAPAGENO:

No mail gateway or no LDAP directory server	All users in PAPAGENO The fax and/or voicemail and/or SMS users will be stored in PAPAGENO. Enter a password in the form of a numeric string for every user to allow access to his messages via phone.
Mail gateway and LDAP directory server	All users in the directory server, gateway user in PAPAGENO. PAPAGENO users are stored in the directory server. In PAPAGENO enter the gateway user who shall receive all incoming faxes and voicemails.
Mail gateway without LDAP and IMAP4 connection but: access to messages by phone shall be possible	All users and all gateway users in PAPAGENO and on the mail server. For users who want to access their messages via phone, all incoming messages, except for those stored in the mail server, must also be saved in the PAPAGENO server. For this, all users and gateway users must be saved in the PAPAGENO server. Distribution of messages takes place according to distribution rules. For access via phone ensure that a password in form of a numeric string is entered for every user in the PAPAGENO server.

A user in PAPAGENO is defined by a **user name** and the **ALPHA server** on which his environment and his documents are administered. This way two identical user names "Johnson" can exist in PAPAGENO if they are registered on different alpha servers.

If you have to register **a great amount of users** we recommend doing this by scripts.

Note: The two user names `comfax` and `FAXADM` exist already and have a special meaning. They cannot be deleted.

If a user name begins with a "." it will **not** appear in the user list. This form of user name is reserved for special users, e.g. for the user `.winpr` handling Windows print jobs, e.g. for the user `.routing` handling Least Cost Routing.

How to Register a New User

- ▶ In the main window of the administration program click in the `Server` folder on the server were you want to register the user.
- ▶ Highlight the `Users` subfolder and click `New...` in the `File` menu to open the `User details` window:

The screenshot shows a 'User details' window with a blue title bar. Inside, there's a 'User' tab selected. Below it, the 'User Name' field is filled with 'keith'. A sub-tab bar shows 'General', 'Send Properties', 'Scan Properties', 'Substitute', 'Actions', 'Background', and 'Extras'. The 'General' sub-tab is active, displaying three fields: 'Comment' with 'Keith Beecham', 'Bar Code' with 'Beecham', and 'Admin. Priority' with '300'. At the bottom, there are three buttons: 'Change Password...', 'OK', and 'Cancel'.

NOTE: If you use a gateway, the only user you have to register is the „gateway user“. You only enter the user name (e. g. `smtpgw`), comment and a password, if required!

User Name	<p>Short term, maximum 10 characters, no spaces or special characters. First character should be alphanumeric.</p> <p>We recommend entering all user names in either lower or upper case.</p> <p>The <code>User Name</code> and the <code>Host Name</code> of the data server (ALPHA) create the database key.</p> <p>Once confirmed with Return, the <code>User Name</code> box no longer can be changed.</p> <p>Confirm with Return.</p>
Comment	Maximum 30 characters,
Bar Code	<p>Enter up to 10 alphanumeric characters (e. g. the name of the user). A barcode will be generated from this entry.</p> <p>If direct dialing numbers are not being used this barcode is important. Faxes with barcode are delivered directly to the owner.</p> <p>A user can add his barcode to documents automatically or manually.</p> <p>A licence is required for bar code option!</p>

Admin. Priority	Priority for the executing of send jobs. Enter a number between 1 and 32000. The higher the number, the higher the preference for a send job...
Change Password	Via button <code>Change Password...</code> Users can enter or change their password in the PAPAGENO user client interface. If a user has forgotten his password a new one can be entered only here.

How to Enter User's Fax Send Properties

The `Send Properties` tab is active only if a user is registered on a local ALPHA server. Send properties for gateway users have to be defined directly in the directory server.

When sending a fax the parameters set for a user have priority to those set for a device!

The screenshot shows a 'User details' window with a 'Send Properties' tab selected. The 'User Name' field contains 'keith'. The 'Priority (%)' field is set to '10'. The 'TSI' field contains '+49 89 54750999'. The 'Pin Code' and 'CPI' fields are empty. The 'Headline' field contains 'VIPcom GmbH \$T\$ \$D\$ page \$p\$ from \$P\$'. At the bottom, there is a 'Change Password...' button and 'OK' and 'Cancel' buttons.

Priority	Percentage value of the administration priority, that is assigned to the user. Users can set their own priority for each send job. If a user works with Outlook via the the PAPAGENO MAPI Connector no entry has to be made in the <code>Priority</code> box. It will be ignored.
Source identifier (TSI)	Fax number with country and area code as well as extension number. Format: <i>+country code_without_0 area code_without_0 phone fax number extension number</i> e. g. +49 89 54750 999 Your fax system will use this for identification when documents are sent.
Pin Code	Pin code for billing in the TC system .

Sender identification(CPI)	This number will be delivered and displayed with each SMS. The recipient can answer if this number is entered as fixed network SMS number. For gateway users the CPI has to be entered in the directory server in the user-specific send properties.
Headline	<p>User specific headline up to a maximum of 80 characters being displayed on all transmitted documents. The following variables can be used:</p> <p> \$\$ Dollar symbols (\$) \$D\$ Date and time, e.g. 18:45 11 March 2011 \$Dxxx\$ Date and time with format. xxx follows the syntax of the time system calls \$T\$ Specific source identification (TSI) \$p\$ Current page (three-digit, preceded by space) \$P\$ Severall number of pages (three-digit, preceded by space) \$N\$ Current job number \$L\$ Modem device name (line ID) \$H\$ Name of the computer (host ID), on which the sender's ALPHA server is installed \$U\$ Name of the user in PAPAGENO (user ID) \$R\$ Dial string before transduction Any additional text will be simply adopted. </p>

How to Appoint a Substitute

The `Substitute` tab is active only if the user is registered on a local ALPHA server.

User details

User Name:

General | Send Properties | Scan Properties | **Substitute** | Actions | Background | Extras


Substitute User:

Keep Copy: ☒

Change Password...

Substitute User	The substitute receives the messages sent to a user. Users can define a substitute in their PAPAGENO user client interface.
Keep Copy	The user keeps a copy of every incoming document.

- ▶ Click on the ... button next to the Substitute user box. to open the User Selection window.



- ▶ In the Server pull down menu select the ALPHA server on which the substitute is registered.
- ▶ The users of these ALPHA servers will be displayed.
- ▶ In the list box select the according user.
- ▶ Close the window with OK.

The substitute's user name will now be displayed in the Substitute user box.

How to Enter Different User Notification Types

This tab is active only if the user is registered on a local ALPHA server.

Users can enter these adjustments in their user client interface except for `Mail address` and `Phone Signal Nr.`

All of these settings can also be specified by the user individually in the user client interfaces. The last entry (either via the administration program or the client) is valid.

Mail, Print, Light, Voice	You can specify whether a user is to be notified by the TC system on receipt and/or dispatch of documents and in the event of errors by mail, by light signals on your phone system, by acoustic signals on your phone system. You can specify to print incoming, outgoing or send failed documents automatically.
Mail Address	Once you have checked mail actions the <code>Mail Address</code> box will be active. You now can enter the address at which E-Mail system users can be reached. Example: keith@vipcomag.de The mail address will be examined by the ALPHA server and must be understood by the operating system of the computer on which the ALPHA server is installed. If you make no entry in the E-Mail Address box, the user name from the Name box will be used automatically as a mail address. If the ALPHA server is running under Windows the „mail notification“ option must be set during PAPAGENO installation in order to use the the mail notification feature. You can change this any time.
Printer	Once you have set the <code>Print</code> actions, the <code>Printer</code> box will be active. Now enter the printer to be used for automatic printing of an incoming, outgoing or failed documents.
Extension numbers	Once you have set actions for light or acoustic signals in the Extension field you must enter the user's extension number.

How to Define Background Paper for the User's Faxes

The tab `Background` is active only if the user is registered on a local ALPHA server.

You can define up to 10 different types of stationery (with company logo, etc.) that users may use as a background to faxes.

In the comFAX client users can enter stationeries, the PAPAGENO MAPI Connector does not support background papers. If the user is working with Outlook background documents do not have to be entered.. The entry will be ignored.

When a user sends a document to PAPAGENO from a Windows application and selects "Paper 1", stationery 1 will be used as a background.

Background documents can also be entered by the users themselves. The last entry (either via the administration program or the client) is valid.

The PAPAGENO MAPI client does not support background documents. If the user is working predominantly with the PAPAGENO MAPI client background documents do not have to be created.

Default	Background document to be used whenever a fax is sent: Enter the number of the desktop document to serve as background in the <code>Standard</code> box.
Paper X	Enter the number of the desktop document to serve as a background in one of the <code>Paper</code> boxes 1-9. Must be selected when sending from a Windows application.

Additional information:

You can enter PAPAGENO **users** of **different company's locations**. This way faxes can be sent for free between users of the according locations.

You cannot enter passwords, email addresses, phone numbers or user specific send properties for users of a remote ALPHA server.

These users are not being charged to PAPAGENO licenses.

The **User** `comfax` is entered automatically during an every ALPHA server's installation.

5. Registering Devices and Device Drivers

Enter each PAPAGENO device with the correspondent driver via the administration program.

The following devices are currently supported by PAPAGENO in combination with the appropriate device drivers:

Use the Service	with the Device	Driver
Fax, Voicemail, SMS	Dialogic card (Eicon Diva card)	gd-capidrv
Fax, Voicemail, SMS	Funkwerk bintec RT1202/ RT3002/ RT4202/ RT4402H	gd-capidrv
Fax	Multi-Tech modem 56k zdx	gd-mdndrv
Fax	US Robotix modem 56k 5630B	gd-mdndrv fm-usrrobot
Fax	Elsa 28,8 56k modem (no longer available)	fm-elsa

Only the ISDN driver `gd-capidrv` supports all three services (fax, voicemail and SMS).

Note: PAPAGENO must have exclusive rights for the devices you set up in the administration program. If other application programs have access to the devices this may seriously impair the performance of PAPAGENO.

6. Setting Up Services in PAPAGENO

Service fax, voice, SMS

- ▶ Enter the device with the correspondent driver in the administrator program (see below 106).

Using fax service :

- ▶ On entering the device, activate the checkbox `Fax` in the tab `General` (see page 107).

Using voice service:

- ▶ On entering the device, activate the the checkbox `Enable Voice` in the tab `Voice` (see page 110).

Using SMS service:

- ▶ On entering the device, activate the the checkbox `SMS` in the tab `General` (see page 107).

Using Fixed Network SMS

SMS messages can be sent to the fixed network direct dialling number of a PAPAGENO user.

- ▶ On entering the device, activate the checkbox `SMS` in the tab `General` (see page 107).

In the device driver the numbers of the Short Message Service Centers are predefined by parameters. These default settings can be changed. (See german Manual „PAPAGENO Installation und Administration für Linux/Unix“, Anh. III „Backend-Geräte“, Kapitel 3. „CAPI-Parameter für ISDN-Geräte“).

Using a directory server:

- ▶ For every user enter the direct dialling number as the user specific sending parameter (`CPI`).

For every user, who sends via MAPI-Connector (Outlook):

- ▶ Enter the direct dialling number as `CPI` (see 98).
On sending an SMS the `CPI` is included. This allows for an answer SMS from the receiver mobile phone.
- ▶ Disconnect the numbers of the Short Message Service Centers in the TC system (Parameter `smc1`),
- ▶ In the Short Message Service Centers (SMS-C) publish the direct dialling number of every user that uses fixed network SMS. This way the number can be activated as a fixed network SMS number.

How Many B Channels are Available?

For every device you enter the number of channels (lines) the device will use.

You have purchased a certain number of channel licenses by VIPcom.

The sum of the channels which you have entered for all devices cannot exceed the number of purchased licenses!

How to check for the available amount of channel licenses:

- ▶ On the left side highlight the folder `Licenses`.
In the right list box besides `Max. lines` you see the maximum number of line licenses at your disposal while next to `configured lines` you see the number of licenses you have already configured.

7. Registering ISDN Cards

Prerequisite: The ISDN card all software and the PAPAGENO THETA server processes are installed!

ISDN cards support **source identifier** and **headline**.

If a user sends a fax, the TSI entered here and the specified headline will be included.

If an individual TSI and headline have been specified for a user, they will be used.

- ▶ In the main window of the administration program click in the `Server` folder on the server system for which you wish to register the device.
- ▶ Highlight the `Device` sub-folder.
- ▶ In the `File` menu select `New....`

Device details

Device

Device Name:

Device Type:

Configured Lines:

Built-in Printer | Scanner Information | Telex Information | Voice | Extras

General | Fax/Dial | Inbound Routing | Accounting | ISDN

Comment:

Physical Device:

User Server:

Enable Options

☒ Fax ☒ Enable Send ☒ Enable Debug Feature 1

☒ SMS ☒ Enable Receive ☐ Enable Debug Feature 2

☐ Enable Speaker

Device Name	Short term, maximum 10 characters, no spaces or special characters.
Device type	<code>gd-capi.drv</code> for a Dialogic Diva Server card. Confirm with Return.
Configured Lines	Number of supported channels (lines). The maximum number of lines must comply with your license!

General tab

Comment	Maximum 30 characters.
Physical Device	Do not enter anything! (Local CAPI will be used.)
Enable Fax	If you want to use the fax service check the option <code>Enable Fax</code> .
Enable SMS	If you want to use the SMS service check the option <code>Enable SMS</code> .
Benutzer-Server (ALPHA)	Since users may be managed on another system, you can select the name of the ALPHA server here. In this case the incoming messages are sent there.
Enable Send, Enable Receive	If messages shall be sent via the device, activate <code>Enable Send</code> . If messages shall be received via the device: activate <code>Enable Receive</code> .
Enable Debug Feature 1, Enable Debug Feature 1	Activate the debug features to check the communication between computer and device. When sending and receiving works correctly disconnect the device!!! The protocol is logged in the file <code>C:\FAXSERVER\logging\drv_device_name</code> .

If you want to enter or change settings for sending fax messages and/or want to enter line type:

- Select the `Fax/Dial` tab

Device details

Device

Device Name:

Device Type:

Configured Lines:

Builtin Printer | Scanner Information | Telex Information | Voice | Extras

General | **Fax/Dial** | Inbound Routing | Accounting | ISDN

TSI:

Headline:

Get Line Type

☐ None ☐ Ground

☒ Dial Strings ☐ Flash

Get External Line:

Get Internal Line:

TSI	Source Identification of your device. Format: <i>+Country code_without_0 Area code_without_0 Fax number and direct dialing number</i> e.g. +49 89 54750 900 If dedicated TSI s have been defined for users those TSIs will be used.
Headline	Maximum 80 characters. Headlines will display automatically on top of each sent document. Variables can be used. If dedicated headlines have been defined specified a special headline for users those headlines will be used.
Get Line Type	In <code>Get Line Type</code> you can specify whether a number is to be dialled for obtaining an external line. If your device is connected directly to an external line select <code>None</code> . If you need to dial a number to reach the public network select <code>Dial Strings</code> .
Get External Line	If you have activated <code>Dial Strings</code> , enter the number that must be dialled to obtain an external line.
Get Internal Line	Features of the of the TC system can be met here. It is possible to enter special characters.

How to Send Fxes Including the CPI

- Select the `ISDN` tab.

The edit boxes in the `ISDN` tab are related to the calling party identification (CPI) which may be included in messages sent via an ISDN device.

Calling Party Number (CPI)	The CPI is included when sending an SMS from this device. Whether you enter only the extension number or the complete phone number depends on which information your TC system passes on.
Calling Party Subaddress	Fax subnumber, if available.

How to Enter Parameters for the Inbound Routing

- Select the `Inbound Routing` tab

Device details

Device

Device Name:

Device Type:

Configured Lines:

General | Fax/Dial | Inbound Routing | Accounting | ISDN |

Inbound Routing

Enable DID: ☐

Min. Digits:

Max. Digits:

Skip Digits:

Wait Digit Timeout:

Number Prefix:

CSI Prefix:

Min. Digits	Counts and enters the number of digists of a phone number that is passed by the TC system or the PBX, example: 3.
Max. Digits	Normally the settings in the <code>Min. Digits</code> and in the <code>Max. Digits</code> boxes are the same. Only when numbers of varying lengths are used the parameters will differ.
Skip Digits	<p>Here you can cut off the subscriber number:</p> <ul style="list-style-type: none"> - if only the direct dialling and extension numbers for users shall be listed in PAPAGENO or in the mail server the TC system or the PBX also passes the subscriber number. - if the number has more than 10 digits. <p>Example: The fax number is 54750-900. If you want to cut off the main number (54750), enter <code>5</code> for the first 5 digits. This means that the last three digits (900) will be passed to PAPAGENO.</p>
Wait Digit Timeout	Enter the time in seconds that the system has to wait for remaining digits, e. g. 10. 12 is the default.

Number Prefix	If you want to enter the complete international phone number for users, even when the system only supplies the direct dialling number or when a number with more than 10 digits has been skipped, you can enter the complete number (optionally with country and area code).here. Example: +49-89-54750
CSI Prefix	The CSI (or CSID = Called Subscriber Identification) is the number the driver returns wen a fax is sent to a destination - the receiptient identification. The sender of the fax sees the CSI on his fax confirmation. The CSI corresponds to the TSI (dispatcher identification), which was entered in the Fax/Dial tab. Enter the same prefix you entered in the Number Prefix box

How to Use Voicemail

- Select the **Voice** tab.

The screenshot shows a window titled "Device details" with a close button. Inside, there's a "Device" section with fields for "Device Name" (eicon), "Device Type" (FAX/VOICE CAPI2.0 (gd-capdrv)), and "Configured Lines" (4) with a "Delete" button. Below this are several tabs: "General", "Fax/Dial", "Inbound Routing", "Accounting", "ISDN", "Builtin Printer", "Scanner Information", "Telex Information", "Voice" (selected), and "Extras". The "Voice" tab contains four settings: "Enable Voice" (checked), "Enable Silence Compression" (checked), "Max. Recording Time" (80000), and "Silence Timeout" (4000).

:

Enable Voice	Activate to use voicemail.
Enable Silence Compression	Activate to compress caller's breaks.
Max. Recording Time	Enter the maximum recording time in milliseconds (e. g. 80000 for 80 seconds).
Silence Timeout	Enter the time (in milliseconds) after which the recording is terminated once the caller finishes speaking (or remains silent) e. g. 4000 for 4 seconds.

How to Calculate Charges

- ▶ Select the `Accounting` file card

Accounting factor	Charge unit as a number (e. g. 12 for 12 Cents)
Accounting Unit	Currency (e.g. <code>Euro</code>), in which calculations should be made. A fictional currency can be entered as well.

To complete your input:

- ▶ Save your entries with `OK`.
- ▶ Register all other fax cards in the same way.

For your settings to become effective,

you have to **stop** and **restart the appropriate drivers to enable any settings or changes**

- ▶ After changing the settings click on `Save` and `Restart`.

8. Registering a PAPAGENO Communication Server

A „PAPAGENO Communication Server“ is a complete configured Windows® system with ISDN functions and a THETA server. This system has already been entered as a server in the administration program.

Since this system is used as device its device data must be entered as well.

- ▶ In the main window of the administration program in the `Server` folder click on the PAPAGENO Communication Server
- ▶ Via the `Device` sub-folder open the window `Device details..`

Device details

Device

Device Name: papageno1

Device Type: FAX/VOICE CAPI2.0 (gd-capidrv)

Configured Lines: 60

Builtin Printer | Scanner Information | Telex Information | Voice | Extras |

General | Fax/Dial | Inbound Routing | Accounting | ISDN

Comment: PAPAGENO computer

Physical Device:

User Server: vpcnw13 (ALPHA Server)

Enable Options

<input checked="" type="checkbox"/> Fax	<input checked="" type="checkbox"/> Enable Send	<input checked="" type="checkbox"/> Enable Debug Feature 1
<input checked="" type="checkbox"/> SMS	<input checked="" type="checkbox"/> Enable Receive	<input checked="" type="checkbox"/> Enable Debug Feature 2
	<input type="checkbox"/> Enable Speaker	

Since the PAPAGENO computer contains ISDN cards, the entry possibilities are the same as described above for ISDN cards.

In the `Configured Lines` field you **enter the total number of lines** configured for the PAPAGENO-Server.

In the **Device Type** field select `gd-capidrv`.

9. Registering a Modem

Modems support source identification (TSI) and dispatching faxes with a headline.

If a user sends a fax via a modem, the TSI entered in the Device Data and the specified headline which are entered in the „Device Data“ will be sent with.

If user-specific TSIs or headlines are defined those will be sent.

- ▶ In the main window of the administration program in the folder `server` click on the server on which the modem is connected.
- ▶ Highlight the `Devices` subfolder
- ▶ In the file menu click: `New`.

Device details

Device

Device Name:

Device Type:

Configured Lines:

Built-in Printer | Scanner Information | Telex Information | Voice | Extras

General | Fax/Dial | Inbound Routing | Accounting | ISDN

Comment:

Physical Device:

User Server:

Enable Options

☒ Fax ☐ Enable Send ☒ Enable Debug Feature 1

☒ SMS ☒ Enable Receive ☒ Enable Debug Feature 2

☐ Enable Speaker

The entry possibilities are the same as described above for ISDN cards (see page 106)

Device Type	gd-mdndrv
Physical Device	Name of the interface(s) (connection between modem and PSTN) e. g. com1, com2 Get the name of the interfaces on the computer the modem is connected to via System Control - Connections.

Enable Speaker	Activate <code>Enable Speaker</code> if you want to listen in the selective process of the modem. That can be serviceable, if some receipients are not available.
-----------------------	---

The `Inbound Routing` and `ISDN` file cards are only available for ISDN devices.

If the modem is voicemail-capable:

- ▶ Make the required entries on the `Voice` tab. (See page 110).

If you want to enter driver-dependent parameters:

- ▶ Enter them in the `Extras` ftab.

10. Enter at Least One Distribution Rule

You must enter at least one distribution rule in PAPAGENO, otherwise incoming messages will not be accepted!

Distribution rule r1:

has already been entered. All incoming messages (provided no other rules have been entered), are sent to the user `comfax`.

You can **change** the **user name** “comfax” (e.g. into “registry”).

If a PAPAGENO **mail gateway is installed** replace the user name “comfax” with the name of the gateway user (e. g. `smtpgw` for SMTP gateway, see Manual „SMTP Gateway“). All incoming faxes will then be forwarded to recipients via the gateway. Exceptions are faxes for which another rule has been defined.

How to Change Distribution Rule r1:

- ▶ In the Administrator’s main window select `Distribution`.
- ▶ Doubleclick on the rule `r1`.
- ▶ In the `Single users` field select a user name respectively the gateway user name.

Other distribution rule options and their hierarchical application by PAPAGENO are described below.

11. PAPAGENO is now ready to use!


Further administration options are described on the following pages.

12. How to Deliver an Incoming Message to Several Users

Create a **user group** including all according users. Register this user group in PAPAGENO and enter a distribution rule.

The distribution rule defines that certain or all faxes and voicemails are to be forwarded to the user group (see below under 13. „Entering Additional Distribution Rules”, page 118).

- ▶ In the main administration program window highlight the folder `User`.
- ▶ Via the menu `File - New ...` open the window `Group Details`



Group name	Short term, maximum 10 characters, no spaces or special characters. Confirm with Return.
Comment	Maximum 30 characters.

To add a user to a group:

- ▶ In `Server` in the pulldown menu select the server were the user is registered.
- ▶ Highlight the desired user name and click the button `<<`
The user name will appear on the left side in `Members`.

To delete a user from a group:

- ▶ In `Members` highlight the user name and click the button `>>`
The user name will be removed from the group.

13. Entering Additional Distribution Rules

Remember:

You have already changed the distribution rule **r1**. A specific **user** or the **gateway user** is registered as the recipient of all incoming faxes.

All incoming faxes will be sent to this user. If the gateway user has been entered incoming messages will be forwarded to the gateway and then distributed to the appropriate recipients.

If user addresses are stored in PAPAGENO (you are **not using a mail gateway** or you are not planning **an IMAP4 connection** to the mail server) each user must be entered in the distribution rules with an appropriate extension number.

Distribution rules to be entered

Apart from rule “r1” you can set up distribution rules by which

- faxes with certain **sender fax numbers**
and/or
- faxes with a specific **direct-dial number**
are forwarded to specific users.

PAPAGENO **processes distribution rules in the following sequence:**

1.	Sender	Direct-dial number	Users/user group
2.	-	Direct-dial number	Users/user group
3.	Sender	-	Users/user group
4.	-	-	Users/ user group

This means that each incoming message will be checked whether there is a rule:

1. for the sender’s number and direct-dial number,
2. for the direct-dial number only,
3. for the sender’s number only.
4. If no rule is applicable to these 3 cases, rule “r1” takes effect. The message will be delivered according to the user entered in this rule or the gateway user.

In this case Only one distribution rule (Rule “r1”). is permitted. If users have direct-dial numbers, option 2. (or 1.) is entered for them in the distribution rules.

Entering distribution rules in PAPAGENO:

- ▶ In the main administration program window highlight the folder `Routes`.
- ▶ Via the menu `File - New ...` open the window `Route Details`

Route Details

Route


Route Name:


Inbound

Comment:


Match Extension:

Match TSI:

User: 

Group: 

Polling

Poll Server: 

Poll Document:


Route Name	Maximum 10 characters, no spaces or special characters. Confirm with Return.
Comment	Maximum 30 characters.
Match Extension	Distribution rule option 1 and 2: - Enter the <code>device name</code> of the ISDN card, modem, ... - Enter the direct-dial number. This number must correspond to the number relayed by the TC system, e. g. 999 or 54750-9-99. Take into account that you may have truncated the number or added a prefix. (see above „How to Enter Parameters for the Inbound Routing“, page 109).
Match TSI	Distribution rule option 1 and 3: Enter the TSI of the calling party or select it from the telephone directory.
User	Select a user from the list with the button ...
Group	Select a user group from the list with the button ...

14. If Faxes Are to be Printed

... enter the printer to be used in PAPAGENO. In the comFAX clients users the available printers are displayed.

A PI server must be installed on each system connected to a printer.

- ▶ In the main administration program window in the folder `Server` highlight the server to which the printer shall be connected.
- ▶ Highlight the sub-folder `Printers`.
- ▶ Open the menu `File - New ...`



Printer name	Maximum 10 characters, no spaces or special characters. Confirm with Return.
Comment	Maximum 30 characters.
Printer Type	Unix printers: Select the convenient printer type. Windows®-Printers: select the printer type <code>MS Windows</code> .
Paper Size	<code>DIN A4</code> , <code>Legal</code> or <code>Letter</code>
Split Page	Only for Unix printers.
Filter Command	Unix printers: Enter a filter command to specify the document location. Windows®-Printers: Enter the exact printer name (as in the <code>Print</code> window in Windows applications).

15. How to Forward Faxes Free of Charge to a Remote PAPAGENO Installation

In order to send faxes free of charge to a remote PAPAGENO installation enter the remote ALPHA server as a remote server. (See also 13., "To Send Faxes Inexpensively from Various Locations", page 40).

Local users then will see the users of the remote installation in their user list. This way they can send documents to them like internal documents - free of charge.

- ▶ In the main administration program window, highlight in the folder `Server`.
- ▶ Via the menu `File - New ...` open the window `Server Details`.

Host Name	Host name of the computer on which the remote ALPHA server is installed.
Comment	Maximum 30 characters.
User Server, Printer Server, Device Server	Activate the box <code>User Server</code>
Network type	Select <code>Wide Area Network</code>


16. How to Use Fax Number Mapping or Call by Call

The front section of specified fax numbers may be replaced by different number. This enables, for example, all foreign faxes to be automatically handled by a specific phone company which is accessed by a certain prefix.

The country- and area code or when required the direct outward dialing can be removed from all fax numbers.

A total of 99 rules can be defined. These are processed until an appropriate rule has been found. Since the administration program will sort the rules automatically their correct sequence must not be considered.

- ▶ Via the `Number Mappings` menu open the window `Number Mappings Details`



Every number must have a prefix:

- **A:** direct outward dialing as specified in the device definition (must also be specified for a direct connection)
- **N:** Internal number within the TC system
- **V:** Distribution within the fax system. Should only appear in the lower input box.

Examples:

Match: A0

Replace: A

removes the direct outward dialing from all numbers.

Match: A089

Replace: A

removes the prefix 089 from all numbers.

Match: A00

Replace: A0103900

dials the call-by-call service number 01039 before the actual call number for all faxes to be sent abroad.

Match: A54750

Replace: N

redirects all calls to the number 54750 directly to the branch exchange.

Match: N2

Replace:V

The PAPAGENO server is connected by the internal number 2. Transmissions to internal numbers beginning with a 2 are not sent by phone line, but directly to the user recognized by the remainder of the number and the specified distribution rules. A fax to the number N250 will be forwarded to the fax user with the (virtual) number 50.

17. Storing Messages in PAPAGENO

If a mail gateway is installed without an IMAP4 connection all incoming messages must be saved on both the mail server and the PAPAGENO server. Otherwise users will not be able to retrieve their messages by telephone.

There are 3 options for doing this.

In all 3 options

- A distribution rule must be entered for every PAPAGENO user:
Every direct-dial number is assigned to a user.
- The gateway user is entered as a user
- The gateway user is entered in the distribution rule “r1” (see 117 above).

Option 1:

The gateway user (e.g. `smtpgw` for an SMTP gateway) is entered as substitute for each user.

All incoming messages are saved in PAPAGENO via distribution rules. All incoming messages are also sent to the mail server via the gateway user as substitute.

Option 2:

In the distribution rule a user group whose only member is the gateway user is assigned to the direct-dial number of a user.

All messages received at this direct-dial number will be delivered to the user and the user group
Mail gateway.

The mail server thus will receive all incoming messages via the gateway user.

Option 3:

In addition to the distribution rules, PAPAGENO can be set to send copies of all incoming documents to the gateway user.

Which of the 3 options you choose...

... depends on which other settings you are going to make.

If a user wishes to nominate a holiday substitute, option 2 or 3 must be chosen, as option 1 does not allow a substitute to be entered.

To record charges choose option 1 or 2 (charges can be calculated with the option “Forward copies of incoming documents to a pseudo user” and a script).

Setting the options:

Option 1

- ▶ For each user enter a distribution rule in which a fax direct-dial number is assigned to the user name. (See above 13. „Entering Additional Distribution Rules”, page 118).
- ▶ For each user enter the gateway user as a substitute.

Option 2

- ▶ Enter a user group whose only member is the gateway user (see also 12. „How to Deliver an Incoming Message to Several Users”, page 117).
- ▶ For each user enter a distribution rule in which the user name is assigned to a fax direct dial number
- ▶ Select the the gateway user for each user in the `user group` field . (see also 13. „Entering Additional Distribution Rules”, page 118).

Option 3

- ▶ For each user enter a distribution rule in which the user name is assigned to a fax direct dial number.
- ▶ In the administration program open the window `Administrator data` and select the option `Retain copies of incoming documents`
- ▶ Select the gateway user as (pseudo) user.

IMPORTANT: To avoid unnecessary waste of hard disk space it is recommended that documents that users do not wish to retrieve by telephone are deleted in PAPAGENO. This is accomplished with the script `a_find_do`.



D. Configure PAPAGENO

1. Connecting PAPAGENO to the Mail System	128
2. Preparing the User Computers	129
3. How to install comFAX/WIn	130
4. How to Install the Fax MAPI Printer	132
5. How to Setup the RedMon Printer	134
6. Configuring Telephone Access to Messages	139
7. How to Install other FAX Clients	140

1. Connecting PAPAGENO to the Mail System

The PAPAGENO **SMTP Gateway** is installed with the PAPAGENO main installation or you have installed it separately (see above Part B1 6. How to Install a PAPAGENO Mail Gateway). Now you have to enable the gateway and set some variables.

- ▶ Enable and set up the gateway .
(See „PAPAGENO SMTP Gateway“ manual.“).

Now users can send documents as faxes and also short messages and voice mails from Outlook. The documents are being converted into fax format either **on the gateway computer** or **on the user computers** via special PAPAGENO printers.

Document Conversion on the Gateway Computer

- ▶ Aktiviate the tools for the conversion of PDF und HTML documents.

The tools `gs_pdftif` and `htmltotif` are located in the PAPAGENO installation directory under `tools`.

If document types except html and pdf should be converted into fax format or if you do not want to use the tools:

- ▶ On the gateway computer install the PAPAGENO MAPI Connector
and
- ▶ install the programs from which users will send documents in the appropriate version.

Document Conversion on the User Computers

See below Kapitel 2. „Preparing the User Computers“, Seite 129.

If an LDAP directory server is in use, you have to register all fax and voice mail users in the directory server.

2. Preparing the User Computers

If Outlook® is used together with a PAPAGENO mail gateway, users can send faxes, short messages and voice mails from Outlook after the setup of the gateway.

If faxes will be converted into the fax format on the gateway computer **you have nothing to do at this point!**

Sending Documents from Windows Applications via User Clients

If faxes should be converted on user computers, you have to install the FAX MAPI Printer. (See also part A, chapter 7 „If No Mail Gateway is Used...”, page 27).

- ▶ Install the FAX MAPI Printer
(See below chapter 4 „How to Install the Fax MAPI Printer”, page 132).
During installation you select the client to which the documents should be forwarded (Outlook, only up to version 2010 or comFAX/Win).

- ▶ If need install comFAX/Win
(See below Chapter 3 „How to install comFAX/Win”, page 130).

A document sent from a Windows application to the FAX MAPI Printer will be converted into the fax format and forwarded to Outlook resp. to comFAX/Win. There you enter the faxnumber and dispatch the document.

Sending Faxes from Applications - without Mail Client

Unix Applications

Documents with send options in form of control commands will be forwarded to special PAPAGENO printers (see Part A, chapter 15 „Sending Dokuments from Applications Directly”, page 42).

The PAPAGENO printers `faxps`, `faxpr` and `faxpspr` are part of the PAPAGENO installation.

Windows Applications

From Windows applications documents will be sent to the free printer software RedMon that converts them into PostScript resp. ASCII format and after this be forwarded to the PAPAGENO printers. (See Part A, chapter 15 „Sending Dokuments from Applications Directly”, page 42).

- ▶ Install the RedMon printer.
(See below, chapter 5 „How to Setup the RedMon Printer”, page 134).

3. How to install comFAX/Win

Prerequisites

- comFAX/WIN builds on Winsock. Ensure that your TCP/IP installation supports this standard. **Winsock.dll** must be supported.

Download Software


- ▶ Download the comFAX/Win software from our Web server: Downloads - PAPAGENO - Components - User Clients - comFAXClient.msi
- ▶ Open `comFAXClient.msi` and follow the installation routine.
After finishing a confirmation message occurs.

Enter a User

- ▶ Doubleclick on comFAX icon.
The comFAX login window will open.

To change the user name:

- ▶ Via settings open the the window `comFAX/WIN-Einstellungen`:



Enter User Name

Only PAPAGENO user names can be entered. Documents sent from local windows applications belong to the user who is entered in `comFAX/WIN-Einstellungen`

- ▶ Enter the user name.

Enter ALPHA host

- ▶ Enter the ALPHA hostname on which the user is entered.

Zu den anderen Einstellungsmöglichkeiten im Fenster comFAX/WIN-Einstellungen siehe Benutzerhandbuch für comFAX/WIN, Teil B, Kapitel 3, „PAPAGENO-Einstellungen“.

4. How to Install the Fax MAPI Printer

The **Fax-MAPI-Printer** is a virtual printer and part of the PAPAGENIO MAPI Connector.

- ▶ Download the actual version of the PAPAGENO-MAPI-Connector from our homepage (www.vipcomag.de - Download - PAPAGENO - Components - MAPI-Connector).

The printer you can install via `setup.exe` (see below on this page) or via a setup command (see below „Install Printer via a Setup Command“, page 133).

In every case you select the client the converted documents will be sent to - **Outlook** (up to version 2010 (32 Bit) or the PAAPGENO-Client **comFAX/Win**. By selecting comFAX/Win you have to enter PAPAGENO user name and ALPHA host.

Installing Printer via `setup.exe`

- ▶ Select the `MAPI` directory
- ▶ Start `setup.exe`.

The following window will open:



- ▶ Select the desired language.


In the `Send via` box you can select the client the converted documents will be sent to.

- ▶ Select `Mail` (Outlook up to 2010) resp. `Papageno` (comFAX/Win)

Attention! Using Outlook 32 Bit you have to select `Papageno`.

- ▶ In the MAPI Installation box select Printer
- ▶ Click OK.

If you have selected Papageno (comFAX/Win) in the Send via box the following window will appear:



- ▶ In the User field enter the PAPAGENO user name in the Alphahost field enter the ALPHA host on which the user is entered.
- ▶ Click OK.

The FaxMAPI Printer will be installed.

Install Printer via a Setup Command

- ▶ Open a DOS box and change to the MAPI directory.

How to use the FaxMAPI Printer setup command :

```
setup mode [alphahost=host user=name] [debug]
```

mode: english, german or french version:

```
printerger printereng oder printerfra
```

If alphahost and user were specified in the command, the printer forwards the converted documents to the PAPAGENO client comFAX/Win, otherwise to Outlook.

- ▶ Enter the FaxMAPI Printer setup command.

The FaxMAPI Printer will be installed.

5. How to Setup the RedMon Printer

„RedMon“ is a free printer software.

Depending on configuration RedMon converts documents from Windows applications to PostScript- resp. to ASCII format and forwards them (via a PAPAGENO-Tool) to a PAPAGENO printer. The printer interprets the control commands, converts the document to fax format and forwards it with all send options to the PAPAGENO driver.

For this see above part A, chapter 15. „Sending Documents from Applications Directly“, page 42.

With „RedMon“ users also can send serial faxes.

- ▶ Download RedMon 1.7 for 32 or for 64 Bit.

<http://redmon.soft-ware.net/download.asp>

After installation you have to setup the printer so that he forwards the document either to a PAPAGENO tool (PostScript) or to a PAPAGENO printer (ASCII)

Setup RedMon as PostScript Printer

- ▶ Log on as administrator on the computer where Redmon will run.

Installing faxps and psscan

To use the PAPAGENO printer client `faxps` and the PAPAGENO PostScript scan tool `psscan`:

- ▶ Install PAPAGENO and deactivate all server processes during installation.
(See also part B, chapter 5. „How to Install a Single PAPAGENO Server“, page 54)

Find `psscan` in the installation directory in the subfolder `tools`, the description in `PAPAGENO_Tools.pdf`.

Activating psscan

- ▶ Copy the `psscan.exe` file and all `.dlls` resp. shared objects in the `/PI` directory.
- ▶ Configure the printer filter `.comfaxpsp`
- ▶ Open a PAPAGENO administrator.

You cannot see the `.comfaxpsp` printer for its name starts with a point, but it exists.

- ▶ Specify a new printer `.comfaxpsp` and ignore the warning that the printer already exists. Confirm.
- ▶ As printer type select: `Postscript`
- ▶ In the `filter` command field enter: `psscan.exe` resp. `psscan`.
- ▶ Save the Configuration and restart the PI server.

Configuring RedMon

- ▶ Extract RedMon17x.
- ▶ Start setup.exe
- ▶ In the control panel in the Devices and Printers section start the assistant to add a new printer
- ▶ Select Lokal Printer.
- ▶ In the Create a new port box select Redirected Port and the name MTP1.
- ▶ Select the driver
<HP Laserjet 2300 Series PS>
It is possible to test and use other PostScript printer drivers.
- ▶ Enter a printer name
(e. g. FAX-PS)
- ▶ Finish the printer installation.
- ▶ Open the printer features
- ▶ Change to the filecard Connections and select MTP1:
- ▶ In the Redirect this port box enter the absolute path to the executive file psscan.exe.
- ▶ In the Arguments for this program box enter the absolute path of the fax directory.
- ▶ Select Run as User.
- ▶ Finish the configuration with OK.
- ▶ Create a test page and print it (see below „Sending a Testpage”, page 136).
Under the user ID fax is created in the outbox of PAPAGENO.

Setup RedMon as ASCII Printer

- ▶ Log on as administrator on the computer where Redmon will run.

Installing faxps

To use the PAPAGENO printer client faxpr:

- ▶ Install PAPAGENO and deactivate all server processes during installation.
(See also part B, chapter 5. „How to Install a Single PAPAGENO Server”, page 54)
- ▶ Make note of the absolute path to the executive file faxpr.exe.
Later you have to enter the path in the printer configuration.

Configuring RedMon

- ▶ Extract RedMon17x.
- ▶ Start setup.exe

-
- In the control panel in the `Devices and Printers` section start the assistant to add a new printer
 - Select `Lokal Printer`.
 - In the `Create a new port` box select `Redirected Port` and the name `MTP1`.
 - Select the driver
`<Generic / Text only>`
 - Enter a printer name
(z. B. `FAX-ASCII`)
 - Finish the printer installation.
 - Open the printer features
 - Change to the filecard `Connections` and select `MTP1`:
 - In the `Redirect this port` box enter the absolute path to the executive file `comfaxpr.exe`.
 - In the `Arguments for this program` box enter the absolute path of the fax directory.
 - Select `Run as User`.
 - Finish the configuration with `OK`.
-
- Create a test page and print it (see below „Sending a Testpage“, page 136).
Under the user ID fax is created in the outbox of PAPAGENO.

Sending a Testpage

The test pages differ relating to the features.

PostScript Printer

The PostScript printer processes RTF and Word documents.

Attention! The arguments in the document (Example: `#PHONE 08954750229#`) must have the colour WHITE! So they stay invisible later.

ASCII Printer

The ASCII printer only processes ASCII documents (Editor resp. Notepad).

The arguments in the document can be printed in black. They will not be displayed later.

Design of a Page - Example:

`#PHONE 08954750229#`

`#USER comfax#`

`#TITLE Testfax über RedMon#`

Hi, this is a test fax via the Windows printer of PAPAGENO
 Hi, this is a test fax via the Windows printer of PAPAGENO
 Hi, this is a test fax via the Windows printer of PAPAGENO
 Hi, this is a test fax via the Windows printer of PAPAGENO
 Hi, this is a test fax via the Windows printer of PAPAGENO
 Hi, this is a test fax via the Windows printer of PAPAGENO
 Hi, this is a test fax via the Windows printer of PAPAGENO
 Hi, this is a test fax via the Windows printer of PAPAGENO
 Hi, this is a test fax via the Windows printer of PAPAGENO

Fax Document Arguments

Below the most important arguments are listed: .

Option	Meaning
#PHONE <i>faxnummer</i> # *1	Fax number of the recipient.
#USER PAPAGENO-Benutzer#	Default user in PAPAGENO.
#ALPHAHOST <i>hostname</i> #	user on another ALPHA server.
#PAPER <i>Schacht</i> #	Paper tray 0 – 9 for the background
#PAPERID <i>Faxid</i> #	Desktop document ID for the background
#PRIORITY <i>Priorität</i> #	Sending priority of the fax. <i>priority</i> must have a value between 1 (lowest priority) and 100 (highest priority).
#RECEIVERGROUP <i>Gruppe</i> #	Receiver group that is entered in the telephone book
#RESOLUTION FINE#	Sending resolution high
#RESOLUTION NORMAL#	Sending resolution low
#RETRIES <i>n</i> #	Number of automatic redialings 1 – 9
#SENDTIME NOW#	Dispatch immediately
#SENDTIME LATER#	Dispatch
#SENDTIME <i>datum / zeit</i> #	Dispatch by entered sending time Syntax: [<i>day.month.year</i>] hour [: <i>minute</i> [: <i>second</i>]]
#TITLE <i>Kommentar</i> #	Comment

*1 Special faxnumber formats are possible:

@@NUMMER *faxnumber*@@

@@PHONE *faxnumber*@@

6. Configuring Telephone Access to Messages

If a mail gateway is used, all faxes and voicemails are stored in the mailserver together with the emails. They are erased from the PAPAGENO database. In this case users **cannot access** to their messages via phone.

For this problem there are two solutions:

- Enter that all incoming messages are stored in the mail server **and** in PAPAGENO .
(Then faxes and voice mails can be accessed via phone)
- Access to the mail server database via **IMAP4**.
(According to the faxes and voicemails even the emails can be accessed)

NOTE: In any case users must have numeric passwords to authorize themselves for the telephone access („pincode“)

If PAPAGENO MAPI connectors are going to be used:

- ▶ Install a MAPI connector on each user's computer.
See manual „PAPAGENO MAPI Connector“.

7. How to Install other FAX Clients

If users want to work only with faxes, except of comFAX/Win we provide to other FAX clients:

- **comFAX/ X Window:** runs under Unix with an X Window interface
- **comFAX/ASCII:** ASCII interface for Unix and Windows® users. (Faxes can be displayed only in a limited way!)

Installation of the fax clients

comFAX/ X Window

comFAX/ X Window is installed together with the basic Unix installation of PAPAGENO or PAPAGENO servers.

comFAX/X Window can be started in a Unix shell **with the Unix ID of a user. X Window must exist.**

comFAX/ASCII

comFAX/ASCII is installed with the basic installation of PAPAGENO or PAPAGENO servers.

comFAX/ASCII can be started at shell level or at the MS-DOS command line.

Index

Symbols

#PHONE telefonnummer# 137
#USER kurzbezeichnung# 137
.profile 68

Numerics

8859 Charset 48, 68

A

a_put_usrconf 58, 76
access messages via phone 83, 139
Accounting factor 111
Accounting Unit 111
Actions file card 101
Admin. Priority 98
Administration program
 - conventions 90
administration program 50, 73
administration programs 87
after installation 69
alias name 14, 66, 67
ALPHA 48, 54, 68, 79
ALPHA server 34, 51, 73, 92, 96
ALPHA Server update 75
ALPHA server update 57
-alphahost 137
Analog 16
ASCII 26, 87, 129, 134
ASCII interface 73

B

Background 102
Background card file 102
background paper 102
back-up concept 35
backup concept 37
Bar Code 97
bash 65
basic installation 67
basic installation, disk storage 15
Benutzername in comFAX/Win angeben 130
Benutzer-Server (ALPHA) 107
bintec 21, 23
BRI 21, 47, 65
Brick 21

C

Call by Call 122
caller's breaks 110
Calling Party Number 108
Calling Party Subaddress 108
CAPI 16, 47, 65
CAPI interface 14, 47, 65
CAPI-VoIP-Protokollstack 20
cellular concept 40
Change Password 98
channel 23
channel license 105
channels 105
character set 72
clients 74
CMD line commands 80
CMD-line commands 54
comFAX 50, 65
comfax 65
comFAX ASCII client 74
comFAX clients installing 62, 84, 140
comFAX/ X Window 62, 84, 140
comFAX/ X Windows 62, 84, 140
comFAX/ASCII 62, 84, 140
comFAX/Win 62, 84, 129
comFAX/Win-Einstellungen 130
comfax-adm 50, 54, 73, 80, 87
comfax-asc 68, 74, 80
comfaxdefault 68, 72
comfaxpr 34, 74
comfaxps 34, 74
comfaxpspr 74
comfax-x 68, 74, 80
commands 51, 73
Comment 92, 97, 107, 117, 119, 120, 121
comment 90
Communication Server 112
communication server 36, 39
company locations. 40
Configured Lines 106
control commands in a fax 129
conversion to fax format 28
CPI 99, 108

D

database 25, 68
Debug 107

- Debug file card 94
- Debug Level 94
- Default 102
- default character set 48, 68
- deinstallation 60, 78
- deliver an incoming message 117
- description 90, 92
- device 22
- device management 34
- Device Name 106
- Device Server 92, 93, 121
- device server 22
- device software 22
- device supports services 21
- Device Type 113
- Device type 106
- devices 21
- devices - installation 61, 81
- devices requirements 13, 15
- Dialogic 21, 23, 106
- Dialogic card 103
- Dialogic Diva-Server-card, installing under Linux 81
- Digital 16
- digital phone system 17
- DIRBUCKETE 58, 76
- DIRBUCKETP 58, 76
- DIRBUCKETS 58, 76
- direct-dial number 118
- directory server 25
- disk space 34
- disk space for faxes 15
- disk storage 15
- disk storage minimum 13
- Dispatch Count 94
- Dispatch Properties 93
- Dispatcher Off 94
- distribution rule 124
- distribution rules 115, 118
- distribution rules - registering 119
- Diva server 23
- DNS name 14
- doc 26
- document conversion 28
- Document Conversion on the Gateway Computer 128
- Document Conversion on the User Computers 128
- driver 54, 80
- drivers 50, 72

DSS1 17

E

- Eicon 23, 81
- Eicon Diva 21
- Eicon Diva card 103
- Elsa modem 103
- Enable Debug Feature 107
- Enable Fax 107
- Enable Receiving 107
- Enable Silence Compression 110
- Enable SMS 107
- Enable Speaker 114
- Enable Voice 110
- Errors in sending documents 101
- etc/hosts 66
- Exchange 25, 47
- Extension numbers 101
- External Line 108
- External Lines 18

F

- Fax 103, 107
- fax 21, 104
- FAX MAPI Printer 129
- Fax Number Mapping 122
- Fax number, replacing by another number 122
- fax server 77
- Fax/Dial 107
- FAXADM 50, 58, 72, 76
- Faxe 20
- faxes sending at the local rate 40
- FAX-MAPI Printer 31
- FaxMAPI Printer - setup command 133
- Fax-MAPI-Printer installation 132
- faxpr 129
- faxps 129, 134, 135
- faxpspr 129
- FAXROOT 68
- faxroot 65
- Filter Command 120
- finish installation 68
- Fixed Network SMS 104
- fixed network SMS 21
- fm-usrrobot 103
- formats to be converted 31
- Forward Faxes to a remote server 121
- Funkwerk 23
- further installations 67

G

- Gateway 128
- gateway 124
- gateway user 97
- gateway, no use 27
- gd-capi.drv 106
- gd-capidrv 51, 73, 103, 112
- gd-mdndrv 103, 113
- General 107
- General file card 92
- Get Line Type 108
- Group 119
- Group Details 117
- Group name 117
- gs_pdftif 128
- GSM device 21, 23

H

- H.323 20
- harddisk 37
- hardware requirements 15
- Hardware requirements (Windows) 13
- Hasler 21
- Headline 99, 108
- headline 106
- high availability 35
- high performance fax transmission 39
- high reliability 36
- Host Name 89, 92, 121
- hosts (file) 66
- HPGL 26
- HTML 87
- html document conversion 29
- htmltotif 128

I

- IIS 87
- IMAP 47, 65
- IMAP4 14, 33, 83, 124, 139
- Inbound Routing 109
- incoming messages 115
- install a single PAPAGENO server 54, 55, 79
- install an update 57, 75
- install_fax 67
- Installation
 - Clients 62, 84
- installation
 - printer clients 80
- installation directory 48, 65
- installation language 48, 67
- installation protocol 48, 68

- installation under Windows 48
- installation under Windows - prior to 47
- installing devices 61, 81
- Installing ISDN cards 61, 81
- installing ISDN cards 61
- installing PAPAGENO under Unix 67
- Internal Line 108
- IP address 66
- IP Phone System 19
- IP-Telefonanlage 16
- ISDN 21, 108, 112
- ISDN card 21
- ISDN cards 61, 81, 106
- ISDN router 18
- ISDN-Karte 16
- isolated area 71

K

- Keep Copy 100
- ksh) 65

L

- l_startdaemon 51, 74
- l_startdriver 51, 73
- l_startdrivers 51, 73
- l_startfax 51, 73
- l_startgateway 51, 74
- l_startserver alpha 51, 73, 93
- l_stopdaemon 51, 74
- l_stopdriver 51, 73
- l_stopfax 51, 73
- l_stopgateways 51, 73
- l_stopserver alpha 51, 73
- LAMBDA 68
- language for user interface 48, 68
- large number of documents 58, 76
- LDAP 14, 33, 47, 65, 83, 128
- LDAP directory server 96
- least-cost-routing 40
- licence key 68
- license key 48
- Light 101
- lines 13, 23, 36, 105
- Linux 15
- local rate 40

M

- Mail 101
- Mail Address 101
- mail gateway 25, 83, 96

- mail notification 48
- mail server 7, 14
- mail server access 83
- MAPI 26
- MAPI Connector 27, 28
- MAPI connector 83, 139
- MAPI-Connector 128
- Match 122
- Match Extension 119
- Match TSI 119
- Max. Digits 109
- Max. Recording Time 110
- messages - storing in PAPAGENO 124
- messages saved in mail server 33
- Microsoft Internet Information Server 87
- Min. Digits 109
- mixed platforms 34
- Modem 16, 21
- modem 23
- Modem - registering 113
- modems 61, 82
- Multi-Tech modem 103

N

- Net Type 93
- network requirements 13, 15
- Network type 121
- NFS 66
- no mail gateway 96
- NTFS 13
- NUE 68
- Number Mappings 122
- number of lines 23
- Number Prefix 110
- Number substitution 122

O

- OMEGA 48, 68
- OMEGA server 89
- operating system 21
- operating systems 15

P

- PAPAGENO Communication Server 21
- PAPAGENO communication server 23
- PAPAGENO device computer 61
- PAPAGENO MAPI Connector 28
- PAPAGENO, ready to use 116

- Paper Size 120
- Paper X 102
- Parallel-Connected External Lines 18
- password 91, 98
- password, changing 91
- PCL 26
- pdf 26
- pdf document conversion 29
- Phone line 123
- Phone System 16
- Physical Device 107
- Physical Device, modem 113
- PI 48, 54, 79
- PI server 34, 92
- Pin Code 98
- platform mix 34
- port mapper. 47
- PostScript 26, 129, 134
- Prefix 110, 122
- Preparing the User Computers 129
- PRI 39, 47, 65
- primary rate interface 39
- Print 101
- print clients 34
- print management 34
- Printer 101
- Printer clients 80
- printer clients 74
- printer clients - installation 80
- Printer name 120
- Printer Server 92, 93, 121
- Printer Type 120
- Priority 98
- private branch exchange 17
- Properties 90
- Protokollstack 16
- psscan 134
- PSTN 38
- public telephone network 47, 65

R

- r1 115, 118
- RAID 37
- ready 116
- Recording Time 110
- RedMon 129, 134
- RedMon als PostScript-Drucker 134
- reduce the main computer's workload 34
- relocation 34

- Remote PAPAGENO Installation 121
- Replace 122
- requirements, Linux/Unix 65
- requirements, Windows 47
- Reserved user names 80
- reserved user names 50, 54, 72
- restart all server processes 95
- retrieve messages by phone 32
- retrival of faxes and voice mails 32
- retrival of faxes, voice mails and mails 33
- rlogin 79
- Route Details 119
- Route Name 119
- routing 50, 72, 96
- RPC services 66
- rpcinfo 66
- RPM package downloaden 81
- RT1202, 23
- runcomfax 68, 75
- runfax 73, 77

S

- S0 18, 21, 22
- S2 22
- S2m 18, 21
- sandbox 71
- scratch 58, 76
- Scripting Engine 22
- SCSI 37
- send jobs 98
- Send Properties 98
- Send via 132
- Sender identification 99
- Sending Documents from Windows Applications 129
- Sending Faxes from Applications 129
- sending faxes inexpensively 40
- serial interface 22
- Serialize Same Number 94
- server
 - registering 92
- server - install single 54
- server install 79
- server processes 50, 72
- set up the Unix user comfax 65
- SETUSER 58, 76
- signature 58, 76
- Silence Timeout 110
- simple backup concept 37
- Skip Digits 109
- slot 22

- SMS 20, 21, 103, 104, 107
- SMTP 7
- SMTP Gateway 83, 128
- SMTP gateway 72
- SMTP-Gateway 25, 50
- smtpgw 97
- software interfaces 52, 74
- software requirements (Unix) 15
- Software requirements (Windows) 13
- source identifier 106
- Source identifier (TSI) 98
- special users 96
- Split Page 120
- standard PAPAGENO environment 72
- start and stop PAPGENO server 56
- start server prozess 95
- start Windows-Administrator 89
- startdriver 51, 73
- startdrivers 51, 73
- startserver 51, 73
- stop server prozess 95
- stop servers 51, 73
- stopdriver 51, 73
- stopdrivers 73
- stopfax 73, 77
- stopserver 51, 73
- subdirectories 58, 76
- Substitute 99
- Substitute file card 99
- Substitute User 100
- system administrator .routing 50, 72
- system administrator FAXADM 50, 72

T

- T.38 20
- t_get_kzg 75
- t_shutdown 51, 73
- TC system 7, 38
- TCP IP 15
- TCP/IP 13, 66
- Telefonischen Nachrichtenzugriff 83, 139
- Telephone Access to Messages 83, 139
- telephone network 47, 65
- telephone network connection 14
- Telex 21
- telex 23
- test pages 136
- Testfax senden (RedMon) 136
- Text-to-Speech 22
- THETA 48, 51, 54, 73, 79
- THETA server 22, 34, 92, 106, 112

TIF 26
Timeout 110
Tools 29
tools 128
transmitted documents 99
TSI 98, 108

U

Unified Messaging 27
uninstall 78
uninstall PAPAGENO 60
Unix 15
Unix Applications 129
Update Version 75
update version 57
update_comfax 75
US Robotix modem 103
User 119
user
 - registering 97
user comfax 50, 65, 72, 79
user groups - registering 117
user management 34
User Name 97
User Notification Types 101
User Server 92, 93
User Server, 121
users
 - registering 96

V

variables 58, 76
VB Admin 53
Voice 101
voice 104
voice box 18
Voice mail 103
voice mail 21
Voice-Mail 20
voicemail 110
VoIP 16
VoIP protocol stac 20

W

Wait Digit Timeout 109
web browser 87
Web-Administrator 87
Wide Area Network 121
Windows 87
Windows 2000 13

Windows Applications 129
Windows-Administrator 53, 87
 - start 89
Windows-Administrator, working with 90
winpr 50, 72, 96

X

X Window client 74
X Window interface 62, 84, 140
xls 26

